

Contents

1	Introduction	3
2	State-of-the-Art of Physically-Based Human Motion Animation	8
2.1	Anatomically Correct Human Figure Presentation	10
2.2	Neurophysiological Aspects of Human Motion	13
2.3	Basic Approaches to Animation of Articulated Figures	18
2.3.1	Kinematics Approaches	18
2.3.2	Dynamics Approaches	22
2.3.3	Motion Controllers	25
2.3.4	Animation of Deformable Objects	29
2.3.5	Motion Planning	33
2.3.6	Autonomous Character Behavior	35
2.3.7	Optimization methods	36
2.4	Motion Editing	39
2.4.1	Processing of Captured Motion	39
2.4.2	Editing Methods	41
2.4.3	Personification	45
2.5	Analysis and Simulation of Specific Motions	47
2.5.1	Terrestrial Locomotion	48
2.5.2	Aerial Movements	55
2.5.3	Arm Movements	57
2.5.4	Miscellaneous Movements	61
2.5.5	Large-scale Numerical Simulation of Human Motion	65
3	Conclusions	67
3.1	Known Problems	67
3.2	Physically-Based Simulation Engine for Animation	69

Computer animation is just a sequence of the objects' images displayed on a screen. There are different classification systems for animation methods. For example, Zeltzer's taxonomy [314] includes guiding, animator-level and task-level animation systems. In guiding systems, the behaviors of animated objects are explicitly described while in animator level systems, they are algorithmically specified. In task level systems, the behaviors of animated objects are specified in terms of events and relationships.

Classification both according to the method of controlling motion and according to the kinds of interactions the actors have has been proposed by Magnenat-Thalmann & Thalmann in [184]. A motion control method specifies how an actor is animated and may be characterized in compliance with the type of information to which it is privileged in animating the synthetic actor. For example, in a keyframe system for an articulated body, the privileged information to be manipulated is the joint angles while in a forward dynamics-based system, the privileged information is a set of forces and torques. The nature of privileged information for the motion control of actors falls into the three categories: geometric, physical and behavioral, giving rise to three corresponding categories of motion control methods:

1. Methods heavily relied upon by the animator: performance animation, shape transformation, parametric keyframe animation. Animated objects are locally controlled. Methods are normally driven by geometric data.
2. Physically-based animations, especially dynamic simulation. The animator should provide physical data corresponding to the complete definition of a motion. The motion is obtained by the dynamic equations of motion relating the forces, torques, constraints and mass distribution for the ob-

DR.RUPNATHJI(DR.RUPAK NATH)

jects. As trajectories and velocities are obtained by solving the equations, motions are globally controlled.

3. Behavioral animation. Control of animation may be performed at a task level or the animated objects can be considered as autonomous creatures.

The last one will probably become a mainstream animation method in the near future. The animation system will accept natural language input and will store libraries of parameterized "self-knowledgeable" characters that can understand the context of the environment and adjust their behaviors accordingly [18].

At present, however, the animation methods are usually divided into three basic categories: keyframing, motion capture and simulation. Sometimes this taxonomy is extended by adding motion editing as a separate approach [98]. Evidently, there is a trade-off between the level of control that the animator has over the fine details of the motion and the amount of work that the computer does automatically.

People are extremely skilled at perceiving the subtle details of human motion. They are able to quickly pick out action that is unnatural or implausible without necessarily knowing exactly what is wrong. Thus humans in computer animations must be natural-looking in both static postures and motion. It takes skilled animators huge amounts of time to produce a quality animation of an articulated figure and integrate a character's motion into a scene. Physically-based simulation is aimed at reducing both time and a required skill of the animator while providing realistic motion. Forces associated with the real world phenomena (gravity, contact forces, torques on joints) are considered along with the physical and physiological properties of the character (masses and inertia moments of the body parts, muscle parameters etc.) and the motion of the character is generated. This is a computationally intensive process, involving the solution of many equations, first to determine accelerations for all the rigid bodies in the scene and then to produce motion over a time step.

Physically-based simulation of human motion can be used for the animation of human figures in two different modes: editing (transformation) of the stored motions and generation of genially new ones:

1. One could name a few actions that could be classified as the motion editing: interpolation between motion captured frames, retargetting the motion to a new character (or to the same one in another mood), adaptation to the variations in the environment (changing the terrain profile, for example), interpolation to produce a new motion by mixing available in the library. The first of these examples is relevant to the keyframing technique as well.

In all these applications the motion transformation could be performed either in a pure geometrical way or be based on the underlying physical laws. The motion transformation based on the geometrical consideration of the keyframe images only (interpolation synthesis, "shape and animation by example", time warping etc.) could result in artifacts such as a figure's distortion (a limb shortening, for example).

2. Producing new animations from scratch could greatly simplify the animator's work reducing it from tedious labour with great number of frames to the script-like programming that specifies the goal of the motion and leaves the generation of the low-level instructions to the system ("George **goes to the bar, takes out a decanter and fills the glasses**"). This type of software is by far more difficult to develop.

The price for this "task-level" animation is, of course, the loss of the animator's control over the subtle details of the motion. However, animators usually don't want just a pure simulation. Animation and simulation have different nature: aesthetics and control are of primary interest for the first one (as has been pointed by Lee [166], the results of simulations are known before they begin). Correspondingly, the elements that constitute animation (modeling, animation, rendering - just mimicking the traditional animation) and simulation (model creation, decision making, temporal management, display building) are different [166].

As was coined by A. Barr, "physics by itself does what it wants to do - it doesn't want to do what you want to do". What animators really want is to guide the models, to be able to specify some amount of control over the motion and then let the rest be automated. Thus one needs both simulation and control to create animation that does what one wants.

The optimal "mixing" of control and simulation in video games is formulated by Helava [116]: the *intended* motion such as running should be ("actively") controlled by the player (and the response time should be short enough to prevent her/him from wandering if the control has been removed from her/his hands) while *unintended* motion (falling, for example, or interaction with an obstacle) should be generated by simulation or physically based motion capture editing¹.

The cardinal question is "What animation is *natural (believable, convincing, realistic)* and are there any objective criteria?". Evidently, in addition to the expert's judgment, one can try to quantitatively compare a simulated motion with either a digitized motion capture or with a simulation based on a "**full**" model using some appropriate norm to measure the deviation. This leads to another question: what is a "**full**" model and could it be made computationally tractable?

One can start with a model of the entire musculoskeletal system as a set of *limbs* considered as rigid bodies connecting *joints* that, depending on their nature, allow limb rotation around one, two or three axes (and gliding of the limb for some joints) **plus** a set of muscle-tendon actuators that represent the basic properties of muscles during force generation. The natural hierarchical model allows one to compute a position of a particular limb by the concatenation of the transformation in all joints along the path from the root limb to the current

¹Some form of "passive" control should be still available to the player in certain circumstances (for example, for coordination of the body's limbs during a fall to make it less painful).

one. The complete model of the musculoskeletal system could be huge (there are about 150 mobile bones and over a hundred hinge, prismatic or ball joints, thus a total number of degrees of freedom for the skeleton alone without accounting for muscles or skin is about 250). However, the model can be greatly reduced for certain types of motions.

One can consider different constraints on the human motion: *anthropometric, physiological, mechanical*.

Anthropometric constraints are formulated mainly as geometric ones. The most common example is the range of admissible angles of the limb rotation in the joint. It should be noted, however, that these limit angles determined by the skeleton structure could be modified for physiological and psychological reasons (for example, flexibility of muscles or existence of "comfortable" limit angles).

Physiological constraints are related to the behavior of the muscle-tendon actuators and could be specified, for example, as force-velocity relations such as Hill law.

To simulate human motion dynamically, we should integrate the laws of mechanics for all components of human model, and, therefore, know all forces and torques. Evidently, the wire-human model could not describe human motion adequately. One should describe in addition the body's mass distribution and the moments of inertia.

Unfortunately, it is not evident if these constraints are sufficient or necessary conditions for the motion to be believable. Evidently, the motion could be anthropometrically valid and obey the laws of mechanics and still look unnaturalⁱⁱ. On the other hand, there is no reason to state that physically impossible motion could not be considered as natural and that is impossible to feign reality. Moreover, it is frequently possible (or even desirable) to exaggerateⁱⁱⁱ the physical effects and thus to produce more "picturesque" motion. Brazel et.al. [28] have suggested to distinguish *physically* plausible and *visually* plausible motions.

The simulation task is complicated by the animator's desire to retain control over the motion, and to this purpose to invert the problem: rather than specify forces and torques acting on the body and follow its motion, she/he wants to get a motion from a given starting position to the final one (inverse kinematic/dynamic technique). Thus some criterion to choose an *optimal* trajectory is needed (minimum power consumption of all the character's muscles, minimum displaced mass or some others).

An essential ingredient of the realistic human motion is *personification*. It could be based on the individual features of the character such as her/his height, weight, some physical defect (lame leg, for example), specific repeated action (adjustment of the glasses, rubbing a cheek etc.). Probably one of the ways to implement this (as well as changing of the character's mood) is via global control

ⁱⁱA very simple example from classical mechanics: the falling of an iron is identical to the falling of a bird's feather in vacuum. Still I am afraid that a lot of people will consider such a motion as unbelievable.

ⁱⁱⁱin fact, exaggeration is one of the basic principles of the classical animation [271]

of the motion's perturbation coupled to the texture mapping as the main tool in achieving personification in *appearance*^{iv}.

The goals of the present study were:

A. To assess the state-of-the-art of the methods for simulation of human motion for animation of human figures as either an editing tool or an automatic motion generator. The following aspects have been considered:

- anatomical and physiological validity of human models
- kinematic and dynamic human motion simulation methods
- control over human motion
- approaches to personification of human motion
- motion editing methods

B. To suggest an approach to development of a hierarchy of mathematical models and efficient simulation methods for producing realistic human motion.

DR. RUPNATHJIK (DR. RUPAK NATH)

^{iv}Luckily, the animation tools are not mature enough to bring into life a nightmare of perfect digital copies of specific individuals forecasted by Badler [18] that inevitably will be drown the Computer Graphics community in the marsh of legal and ethical problems.

Chapter 2

State-of-the-Art of Physically-Based Human Motion Animation

The length of a progress report is inversely proportional to the amount of progress.
More Murphy's Law

Keyframing requires that the animator specifies critical, or key, positions for the objects. The computer then fills in the missing frames by smoothly interpolating between those positions. This method requires the animator to possess a detailed understanding of objects' motion as well as a skill to express that information through the keyframed configurations. The continued popularity of keyframing comes from the degree of control it allows over the fine details of the motion.

In motion capture magnetic or vision-based sensors record the actions of a human subject in three dimensions. Afterwards stored data could be processed for animation of an articulated figure. This method is used widely since many commonplace human actions can be easily recorded. However, it has a number of intrinsic limitations. It is difficult to record certain movements: motion capture has the same restrictions as live actors plus a few specific ones. Shifting of markers placed on skin and clothing as the human moves produces errors in the data. Magnetic systems often require the subject to be connected to a computer by cables, restricting the range of motion. Optical systems have problems with occlusion caused by one body part blocking another from view. Another problem is difficulties of automatic distinguishing the reflectors when they get very close to each other during motion. These problems may be minimized by adding more cameras. And last but not the least, to be useful for editing, the captured motion should be "projected" onto the articulated human model (see a brief discussion of this problem below).

As a technique for generating human motion, physically-based simulation has two potential advantages over keyframing and motion capture. Firstly, simulations can easily be used to produce modified motion while maintaining its natural-looking character. Secondly, real-time simulations allow interactivity, an important feature for virtual environments and video games in which artificial characters must respond to the actions of a player. In contrast, applications based on keyframing and motion capture select and modify motions from a pre-computed library of movements. This advantage is probably the most important for animation of a transition from a specific motion to another one (for example, falling of a running human).

A general hierarchy of the human models for animation has been proposed by Funge [93]:

- Geometric
- Physical
- Biomechanical (musculoskeletal)
- Biomechanical (neuromuscular)
- Behavior (low-level behavior)
- Cognitive (high-level behavior)

Badler [21, 20] introduced a notion of *virtual fidelity* and listed five dimensions that could be used to measure the quality of human animation:

1. Appearance: 2D drawings \Rightarrow 3D wireframe \Rightarrow 3D polyhedra \Rightarrow curved surfaces \Rightarrow freeform deformations \Rightarrow accurate surfaces \Rightarrow muscles, fat \Rightarrow biomechanics \Rightarrow clothing, equipment \Rightarrow physiological effects (perspiration, irritation, injury)
2. Function: cartoon \Rightarrow jointed skeleton \Rightarrow joint limits \Rightarrow strength limits \Rightarrow fatigue \Rightarrow hazards \Rightarrow injury \Rightarrow skills \Rightarrow effects of loads and stressors \Rightarrow psychological models \Rightarrow cognitive models \Rightarrow roles \Rightarrow teaming
3. Time: off-line animation \Rightarrow interactive manipulation \Rightarrow real-time motion playback \Rightarrow parameterized motion synthesis \Rightarrow multiple agents \Rightarrow crowds \Rightarrow coordinated teams
4. Autonomy: drawing \Rightarrow scripting \Rightarrow interacting \Rightarrow reacting \Rightarrow making decisions \Rightarrow communicating \Rightarrow intending \Rightarrow taking initiative \Rightarrow leading
5. Individuality: generic character \Rightarrow hand-crafted character \Rightarrow cultural distinctions \Rightarrow personality \Rightarrow psychological-physiological profiles \Rightarrow gender and age \Rightarrow specific individual

Evidently, the relative importance of these parameters depends on the application.

2.1 Anatomically Correct Human Figure Presentation

The head sublime, the heart pathos, the genitals beauty, hands and feet proportion
William Blake

The basis of believable human motion is a correct representation of the human figure. One can distinguish two aspects of a realistic human model: its resemblance to the anatomically plausible structure (first of all in the topological sense) and the richness of a model in details (human figures have been animated using a variety of geometric models including stick figures, polygonal models, and NURBS-based models with muscles, flexible skin, or clothing). It is interesting to note that while the simulated motion does not look as natural as that of real people, for the time being, some viewers do choose simulated motion as more natural when both types are viewed with the human bodies removed so that the movement is shown only as the dots located at the joints.

Evidently, blunt errors in correspondence between articulated skeleton and real human one should more explicitly manifest themselves in motion than in static postures. As an example, animation of the golf player described by Henry-Biskup [117] could be mentioned. The model was attached to a rather simple articulated skeleton driven by motion captured data. It is turned out that the golfer posture during bending is very stiff and unnatural, thighs seem to be too long and the shoulders ballooned out. All the attempts to improve appearance by changing vertex attachments and editing link parameters failed. The problem was solved by examination of the underlying skeleton structure and its modification. First of all, a coplanar arrangement of two hips and back joints on one horizontal plane was changed to more anatomically motivated one with lowered hip joints. The second necessary modification was raising of the shoulder joint.

Another example is the spine modeling. Spinal column consists of 24 movable vertebrae [30]. The accumulation of each vertebrae's small rotations results in considerable bending and twisting. The spine connects three large bony masses of the skeleton - the skull, rib cage, and the pelvis. Ratner [235] stresses that generating realistic motion required an adequate description of the action of the spinal column and its effect on the torso. General aspects of the biomechanically sound approach to the human motion have been discussed by Zatsiorsky et.al. [311].

It should be noted that due to the hierarchical structure of the human figure the error is more dangerous the closer it is located to the root.

An advanced model of an articulated figure based on biomechanical data is described by Savenko et.al. [248]. The authors state that the usual hierarchical model of articulated figures in animation assumes that all joints having more than one degree of freedom can be effectively represented as several hinge joints connected by zero-length links. Thus the motion in such a joint can be modelled as two or three successive rotations about axes of the fixed orthogonal reference

frame.

This type of model is highly suited for robotics, where the joints are carefully constructed to have a prescribed number of degrees of freedom, but this does not guarantee that it is appropriate for figure animation. It is obvious that the structures of real joints are quite different from those of mechanical joints.

The following assumptions are usually made in the models of an articulated figure:

- the axes of the joints are parallel to the anatomical axes of the figure, i.e. all basic motions in a joint with one degree of freedom are performed in either the frontal or the sagittal (vertical plane which divides a body into two symmetric parts) or the transverse (horizontal) planes
- the axis of rotation of a joint does not change during the motion

However, for some joints the inclination of the axis in one or two planes can be as large as up to 40° [248].

A joint is a bodily component used to connect the bones of the skeleton. Apart from connectivity, joints also provide mobility and stability. The structure and function of joints are closely related. The structure defines the character and range of motion available to the joint. A joint capsule encloses the ends of the bones and thus connects them, but not in a rigid manner. In order to obtain additional stability and strength for a joint, the bones are also connected by ligaments.

Most joints in the human body permit some form of motion and are divided into three groups: uniaxial, biaxial and multiaxial on the basis of the motions which can take place. This classification is simplified; most joints show supplementary motions (both rotational and translational) of small amplitudesⁱ. These motions, called combined, occur unconsciously, with little (if any) participation of the central nervous system [134]. The joint surfaces and ligaments are playing the dominant role. For example, the internal rotation of the lower leg associated with the knee flexion (with an amplitude about 15°) is controlled by the knee ligaments and asymmetry of the knee joint surface morphology. However, the primary motion of the knee flexion is performed voluntarily.

The axis of rotation does not stay the same, but continually changes throughout the motion [89, 248]. However, a single stationary axis is a reasonable approximation for many joints. The idea of an *instant* axis of rotation can be used to model complex simultaneous motions in a multiaxial joint. For instance, a motion in the hip can be modelled either as a sequence of three rotations about three axes or as a single motion about the instant helical axis.

Sometimes a combined motion can occur in the joint. For example, a coupled rolling-sliding motion is observed in a human knee during flexion [180]. Evidently, the most accurate (but computationally intensive) method to study joint motion is numerical simulation of a free joint (no fixed restriction on the degrees of freedom) using finite element representation of the bones in contact

ⁱThere is an opinion that inability of the joint prostheses to allow such motions is one of the main reasons of their long-term failure [134].

[89]. Effective restriction of the degrees of freedom will be provided by contact forces between bones and by ligaments and muscles.

A simplification of the anatomical structure is used often when gross motion is simulated. For example, the shoulder complex, which refers to the combination of the glenohumeral joint and the shoulder girdle including the clavicle and scapula and their articulations, has been studied in detail in [176]. The model contains four bones (thorax, clavicle, scapula and humerus) together with four articulating joints. Twenty-two muscles serve the shoulder mechanism and provide the variety of motions of the human upper limb. The greater part of these muscles are broad and have no unique line of action. Thus for modeling these muscles with large attachment areas splitting into several elements should be used. In the cited paper thirty-six elements have been considered as the stretched strings and the muscle forces have been assumed to act along these direct lines. It should be noted, however, that in reality many of the muscles follow the contours of the body structures and, therefore, would be better modelled as the curved elements [285]. Nevertheless, such complex structure as the shoulder girdle could be reduced to a "lumped" spherical joint between thorax and humerus [290] when the gross human motions of interest.

A description of the general aspects of the human joint geometry and kinematics as well as information on the twenty-six specific human joints can be found in a book by Zatsiorsky [310]. A detailed modeling of the upper human limb has been performed by Maurel [187, 188].

The skeleton being defined, one has to divide human body into segments (which is not a trivial task as explained in detail by Hatze [114]) and to determine parameters of these segments. Among these parameters mass, volume, density, position of the centre of mass and moments of inertia should be mentioned. Bjornstrup [36] reviewed the methods for measuring of the body segment parameters starting from probably the first registered work by Borelli (1680). He also gives references to a number of published papers that contain measured results for different parts and for the whole human body.

Kepple et. al. [145] have examined the muscle attachments from 52 skeletons and suggested the locations of idealized muscle attachments on the pelvis, femurs, tibiae and fibulae, and feet. Statistical accumulation and scaling techniques have been used to generate highly representative normative models, which have been divided into groups and tested for differences based on gender and race. From the test results, the pelvis was divided into a male model, a black female model and a white female model. The foot was separated into black and white models. Single models were used for the femur and the tibia/fibula.

A requirement for the complexity of a universal human articulated figure has been suggested by Boulic & Mas [43]. The authors assume that one needs at least 30 DOFs for extremities alone plus 12 DOFs for a crude representation of the relative motion of the pelvis, abdomen, thorax, neck and head. Thus, even excluding the mobility of the clavicle and scapula, the model should contain 42 DOFs. Additional 40 DOFs are needed for a simplified description of the hands. Adding 8 to 12 DOFs for animation of the clavicle and scapula and a

few DOFs for "aggregate vertebrae" to provide spine bending one would get over 120 DOFs depending on the resolution of the spine model.

This model is in close agreement with that of Hatze [114] who assumes that for the simulation of gross body motions a 17-segment figure is optimal (abdomino-pelvic segment, abdomino-thoracic segment, head-neck, left and right shoulders, arms, forearms, hands, thighs, legs and feet). The model has 42 DOFs (3 linear and 39 angular generalized coordinates).

2.2 Neurophysiological Aspects of Human Motion

If you can force your heart and nerve and sinew
To serve your turn long after they are gone

Rudyard Kipling

Humans move easily with little conscious thought. This ease, however, is deceptive. It is a wonder, given the complexity of the musculotendon system and of control processes that coordinate muscles activity, that a human can move at allⁱⁱ.

The systematic analysis of the control of human motion is certainly beyond the present review (see, for example [210] and the references therein). In what follows a few not-too-well-structured remarks are given.

To develop an adequate biology-based model one has to know the structure and properties of the neuromuscular system and to understand the principles of its operation. Van der Helm [286] has listed the needed data:

- the linkage system (bones, joints, ligaments) with the associated mass and viscoelastic properties
- the actuator system containing the muscles
- the sensory system with the muscle spindles and Golgi tendon organs
- the control system at various levels of the central nervous system

A primary role of muscles is to produce forces as a result of contraction and thus provide joint torques that cause limb movements. Evidently, correct description of the muscle properties is essential for simulation of human motion.

Muscle modeling should include two steps:

1. determination of the muscle line of action and/or muscle moment arm
2. simulation of the muscle dynamics

ⁱⁱremember a malignant snail that asked a centipede about the order it moves its legs in

There are a number of different definition of the line of action. The two obvious ones is straight line and centroid line approaches. Maurel [187] suggested a *contour* line method and van der Helm [286] - a *bony contour* approach. Muscles with broad attachments should be divided into several bundles.

The force produced by muscle is determined by its size and structure, the contractile conditions (length and speed of contraction) and the character of activation. The force is usually assumed to be proportional to the physiological cross sectional area (PCSA).

The dependences of the muscle force on the level of activation, length, velocity have been studied by numerous researchers [118]. The best known one is by all means Hill's force-velocity relationship [120]. It should be noted, however, that it is valid for maximally activated muscle, isotonic shortening contractions and at the optimal length of the muscle. The fact that the force-velocity relationship is not an intrinsic muscle characteristic has been recently confirmed by Ettema and Meijzer [86]. The authors have compared a modified Hill's model and an "exponentially decay model" and conclude that both well describe short contractions (300-500 ms) and less accurately long duration behavior. Since exponentially decay model does not incorporate a force-velocity curve, the authors argue that this relation is not a fundamental property of muscle in contrast to, for example, the length-tension curve.

Phenomenological Hill's model that includes a contractile element, a series elastic element and a parallel elastic element or its modifications are used in the majority of works. The relation of the muscle properties (active and passive length-tension, isotonic force-velocity) to the anatomical structure of muscles has been studied by Lieber [173]. A comparison of the Hill model with the distributed moment model based on the cross-bridge theory of muscle contraction for iso-velocity stretches performed by Cole et.al. [71] have shown that the former model is preferable in the cases considered. A model accounting for the details of muscle activation (time pattern of the stimulation interpulse interval, pulse width and pulse amplitude) has been developed by Riener & Quinern [239]. Three anatomy based muscle models have been constructed and applied to the muscles of the arm and torso by Scheepers et.al. [250].

A thermodynamic analysis of the muscle contraction in which muscle, not an individual myosin crossbridge, is considered as a near-equilibrium system has been applied by Baker & Thomas [23] to a simple two-states cross-bridge scheme [131]. As a result the authors have been able to provide a theoretical basis for an empirical Hill's equation.

An advanced computational approach to modeling the complex mechanical properties of muscles and tendons under physiological conditions of recruitment and kinematics has been developed by Cheng et.al. [64]. The model is based on recently published data on muscle and tendon properties measured in feline slow- and fast-twitch muscle, and incorporates a novel approach to simulating recruitment and frequency modulation of different fiber-types in mixed muscles.

It should be noted that practically all the papers devoted to the muscle contraction simulation (based on either simple Hill-type models or more elaborate ones that account for excitation dynamics) assume muscle uniformity. Thus it

is possible to consider "lumped" model consisting of a few zero-dimensional elements. In reality, muscle is far from being uniform, especially in cross-sectional area and activation pattern. Its contraction should also be nonuniform as has been proved by continuum one-dimensional computations performed by Aigner & Heegaard [4].

Accurate simulation of the tendon is almost as critical as that of muscles themselves. Tendon compliance is important because it causes the length and velocity of the contractile element to be out of phase with those of the whole muscle. For example, in an active muscle with a high ratio of tendon-to-contractile element length, a stretch to the whole musculotendon system would only slightly lengthen the contractile element, with the majority of the length change being accommodated by lengthening of the tendon [309]. In fact, under certain conditions, the musculotendon element can be lengthening while the contractile element within the muscle is shortening, or vice-versa. This behavior would be misrepresented in tendon-less models, which assume that contractile length changes are proportional to path length changes. The tendon and the contractile muscle fiber elements both act on a muscle mass that provides inertial damping to prevent instabilities arising within the muscle model [178].

A Hill type model that accounts for nonlinear static and dynamic properties of both muscle and tendon have been used by Riener et.al [240] to develop a model of the human knee. Muscle fatigue and passive muscle viscosity have been incorporated into the model.

Zajac [309] has advocated a model that defines the properties of a generic musculotendon element with a single set of equations. The five parameters required by Zajac's equations are optimal fascicle length (the length at which the muscle produces maximal tetanic isometric force), maximal tetanic isometric force, pennation angle of the muscle fibers at optimal fascicle length, time-scaling parameter for maximal muscle shortening velocity and rise and fall times, and tendon slack length. Once these measures had been determined for a given muscle, its behavior could be reproduced mathematically.

A special attention should be paid to ligaments. The high stiffness of ligaments result in a high sensitivity of the ligament forces to the joint motions. For the inverse dynamic simulations it is virtually impossible to include ligaments, in forward dynamic ones the stiffness of ligaments is a major factor determining the size of the time step [286].

The most inconvenient feature of the musculoskeletal system for the numerical simulation is by all means *redundancy*. One should distinguish an actuator and kinematic redundancies. The first one is in that more than one muscle controls one degree of freedom (DOF). For example, for a simple hinge joint with 1 DOF there are two muscles (agonist-antagonist). Muscle can co-contract: while the net moment at the joint could be constant, the forces of the muscles change. Kinematic redundancy means that there are more DOFs in the joints than at the end-effectors (for example, arm can move when a hand is holding a handle).

The aim of the study of motor control is to determine how the central nervous system effects functional, goal-directed movement [263]. A central issue for

understanding human motion is how the excessive degrees of freedom of the neuromuscular system are controlled [31]. Usually the mechanisms involved in motor control are presented as a hierarchy, with the brain at the top, the spinal cord in the middle, and the musculoskeletal system at the bottom [178].

The importance of the muscles simulation for the correct description of the movements themselves is evident. However, it seems that their role is not restricted to the producing force. Full & Koditschek [91] have studied the significance of the neural and mechanical systems in the locomotion control. The conclusion is that the slow, variable-frequency motion is dominated by the nervous system while the role of the mechanical system is significant in the control of the rapid, rhythmic movements. As has been noted by Raitbert & Hodgins, "the mechanical system has a mind of its own" [234].

Wagner & Blickhan [288] have studied stabilizing properties of skeletal muscles, i.e. their ability to damp the oscillatory movement ("preflex") without reflexive changes in activation. Four muscles model have been considered: "Hill-simple" (just the contractile element), "Hill-SEG" (an additional serial-elastic element), "Hill-PEC-DC" (an elastic element and a damper connected in parallel to the contractile element), "Hill- $E(t, X, V)$ " (the contractile element is activated by the function representing a displacement and velocity sensitive controller). The authors conclude that self-stabilizing ability of the musculoskeletal system is significant only if the muscle properties (force-velocity and force-length relationships) are tuned to the geometric properties of the linkage system.

One of the most remarkable features of the human motion is the synergies in operation. Synergy is the working groups of neurons, muscles, joints as if they were a single entity. This notion was introduced by Bernstein [31] to cope with the problem of muscle and kinetic redundancy. An example of synergy is a linear relation between elbow and shoulder dynamic torque in natural pointing movements [307].

Locomotion involves repetitive movements and is often executed unconsciously and automatically. In order to achieve smooth locomotion, the coordination of the rhythms of all muscles is necessary. Neurophysiological studies have revealed that basic rhythms are produced in the spinal network called the central pattern generator (CPG), where some neural oscillators interact to self-organize coordinated rhythms.

Review of the experimental evidence for existence of CPG in cats and primates (including man) can be found in [82].

Recent experimental results indicate that decerebrate cats have the ability to learn new gait patterns in a changed environmentⁱⁱⁱ [133].

In the last years it has become possible to regain some locomotor activity in patients suffering from an incomplete spinal cord injury through intense training on a treadmill. Non-patterned electrical stimulation in subjects with complete, long-standing spinal cord injury, can induce patterned, locomotor-like activity

ⁱⁱⁱHowever, this does not include situations when the motor cortex is involved in anticipatory gait changes due to visual input (decerebrate cats cannot step over obstacles)[265]

[80]. This finding suggests that spinal circuitry in humans has the capability of generating locomotor-like activity even when isolated from brain control.

The evidence for the low-level muscle control by primary motor cortex and resolution of the seeming contradictions with experimental data is discussed by Todorov [272].

There is increasing agreement that the cerebellum plays an important role in motor learning [260]. A unique characteristic of motor learning is that it adjusts joint and limb mechanics by altering the neural input to muscles through practice and mental rehearsal. Smith [260] proposed a hypothesis that the cerebellum plays an important role in motor learning by forming and storing associated muscle activation patterns for the time-varying control of limb mechanics. Optimal control cannot be achieved by online corrections initiated by reflex feedback because of the delays and consequent instabilities incurred.

A discussion is under way about the use of representations (internal models) to explain how intelligent behavior is generated. These models are used by the subject to instruct the motor apparatus. So-called interactionists do not accept the existence of internal representational models. One of the problems non-representational approach faces is a difficulty with explanation of the anticipatory, future oriented behavior. Keijzer [144] has made an attempt to extend the interactionist conceptual framework by the analysis of anticipatory behavior as a process which involves multiple spatio-temporal scales of neural, bodily and environmental dynamics.

However, the available data strongly support the existence of internal models for motor control and trajectory planning [143]. Moreover, it is shown that cerebellum should contains internal models of different types [299]. Forward internal models predict the consequences of actions and could overcome time delays associated with feedback control. Multiple paired forward and inverse models play an important role in motor learning.

Human ability to imitate is not well understood but a powerful form of motor skill learning. Evidence from neuroscience indicate that there are two neural structures that are of great importance to imitation. The first one is *spinal fields* that contain code for the primitive motions [35]. (i.e. stereotypical movements invariant to the exact position and the rate of motion). Primitives can be combined to produce a meaningful motion. The second one is that appear to directly connect the visual and motor control systems by mapping observed motions to the motor structures [241] *mirror neurons*^{iv}.

These findings have been exploited by Billard & Matarić [34] for the development of the imitation based control system for humanoids robots. The motor control in this system is hierarchical with a spinal form module at the lowest level and cerebellum modules responsible for the motion learning are at the highest one.

A mathematical model of the spinal motor control system (SMCS) has been developed by Shimansky [257]. The author has shown that an internal rep-

^{iv} mirror neurons have been shown to fire both when the monkey grasps a banana and when it observes another monkey or a human performing a similar grasp

resentation of the controlled object exists already at the level of SMCS. This system is able to generate motor patterns for reflex rhythmic motions such as locomotion without the aid of the peripheral afferent feedback and can modify its activity in response to peripheral afferent stimuli.

Hatze [115] has considered the myoskeletal and myocybernetic control problems and have shown that, while both of them ill-posed, the latter is unsolvable in the present formulation ("find neural control that generate observed motion"). This is explained by the hyposensitivity of the skeletal movements to the neural control input perturbations.

2.3 Basic Approaches to Animation of Articulated Figures

Man will occasionally stumble over the truth, but most of the time he will pick himself up and continue on.

Winston Churchill

The literature on computer animation is vast (for example, a list of references published by Magnenat-Thalmann & Thalmann in 1992 [185] contained 600 entries) and its comprehensive review is by all means beyond the present report. We are going to focus on the issues closely related to those approaches to human motion editing/synthesis that rely heavily on biological knowledge and physical laws. Moreover, we will not touch at all such topics as texture mapping and face animation [218, 291], and cloth [25, 83, 205, 223] modeling. The review, being restricted in such a way, still will be certainly incomplete. Some sections will inevitably be sketchy. We hope to outline basic trends and approaches only and illustrate them by a few typical examples, not bothering with establishing priorities of different researchers. The division of the research topics between subsections is rather arbitrary (for example, motion editing can incorporate elements of physically based simulation; it is unclear what subsection the studies of free form deformations or agent's path planning belong to). Mathematical details will be avoided wherever possible since they are, as a rule, not animation specific and can be found in standard references.

2.3.1 Kinematics Approaches

As speed increases objects can be in several places at once.

Cartoon Laws of Physics

In kinematics, an articulated figure is a set of rigid bodies whose motions are restricted by the linkages among them. The state of the system can be defined as a union of the states of the bodies; the state of the body is just its position and orientation. Linkages (joints) are reducing the total number of degrees of freedom (DOFs) of the system. In practice the figure is usually described in an

hierarchical way [53] and is organized in a form of a tree; the nodes of the tree correspond to the links, and the edges correspond to the joints. The purpose of the joint connecting two links is to perform a transformation of one link relative to another. Thus the absolute position of a particular link can be calculated by concatenation of the transformations in all joints along the path from the root link to the current link. Thus the state of the figure is given by the position of its root and the joints angles (one to three, depending on the joint type) [58, 223].

The figure's motion is a rather rich problem for mathematicians. While the motion of a single rigid body is well understood (see the book by Arnold [15]), the theory of multibody dynamics is still under development (for example, a recent paper by Park & Kim [219] where coupling of the Lie group techniques and Riemannian geometry has been exploited to study metric characteristics of a generalized inertia tensor of the system and approaches to its factorization for both open and closed kinematic chains^v)).

There are different approaches to mathematical description of the figure articulations. Matrix method allows one to define both the translation and the rotation of the local system fixed to a body and, thus, the position of the object in the different systems and its displacement can easily be defined. The components of the *rotation matrix* are *direction cosines* of the local system relative to the global one (direction angles are the angles that a vector makes with the coordinate axes). Combining translation and rotation one gets the *transformation matrix*. The body motion can be presented as a sequence of the rotations and translations.

Nine direction cosines are, evidently, redundant, since the orientation of the body in space is determined by a smaller number of parameters. Three independent angles corresponding to the three rotational degrees of freedom (*Euler angles*) need to be determined^{vi}. Rotations in 3D space are noncommutative: changing their order will change the final body position. A specific order of the Euler angles is usually used in biomechanics [310]: precession (in the sagittal plane), nutation (away or towards the sagittal plane) and twist, or spin (along the axis fixed within a body). Sometimes the so-called *nautical* angles (yaw, pitch, roll) are used. In total, there are 12 different combinations of rotations that can produce a given spatial orientation.

For the particular angular positions a singularity ("gimbal-lock") occurs: two axes become parallel and Euler angles could not be determined (effectively, one degree of freedom is lost). Another drawback of using Euler angles is the jerky, unnatural motion produced when one interpolates Euler angles between different positions [13].

The screw (helical) method based on the Chasles' theorem ("Any motion of

^vNote, however, that Žefran et.al. [312] have shown that no Riemannian metric exists whose geodesics (a generalization of straight lines in Euclidean space to Riemannian manifolds) are screw motions between two positions of a rigid body and semi-Riemannian metric is more appropriate for description of such motions.

^{vi}Euler theorem states that "Any motion of a rigid body with one point fixed is a single rotation around an axis through that point".

a rigid body can be obtained as the rotation around an axis and the translation along this axis”) permits a description of the body motion without referring to arbitrarily chosen axes of rotation [310]. At any given instant there exists a line (*screw*, or *helical line*^{viii}) that keeps its position in space and the translation and rotation occur along and around this line. The following six parameters are required to define the body position:

- two coordinates of the piercing point of the helical axis with one of three coordinate planes
- two direction cosines of the helical axis
- body translation along the helical axis
- body rotation about the helical axis

When helical axis method is used to describe rotations, only three parameters are needed. One can use either four Euler’s parameters subjected to a constraint equation, Rodriguez’s parameters or quaternions. Formally, the latter can be written as a sum of a scalar and a vector with Euler’s parameters as coefficients.

Quaternions are assumed to be superior over traditional matrix methods for intensive computations with 3D rotations [43]. Hestens [119] advocates the use of quaternions in the frame of *geometric algebra* developed by the author . This description is invariant (meaning coordinate-free) and, as the author argues, facilitates the analysis of different control variables and kinematic constraints.

In fact, geometric algebra is just another kind of symbolic notation. Its main advantage over the classical vector and tensor notation is the simplicity of the formulae and absence of numerous indices typical for the tensor calculus. However, this notation is not a new and cutting-edge technique. It is based on the quaternion calculus and just applies the classical duality theory to this finite-dimensional space. Invariance of this approach is very useful for symbolic manipulations. It is claimed in the cited paper, that geometric algebra is computationally superior in comparison with the classical vector and tensor notations. But computations themselves are based on the Frenet’s basis notation, not the geometric algebra. Probably this claim means that if one uses geometric algebra for the symbolic manipulation, the formulae obtained are simpler (even in the terms of spherical trigonometry) than ones obtained with tensor calculus. This statement is perhaps true, because the main advantage of the geometric algebra as a symbolic language is existence of so called *spinors* that define rotational transformations. Such objects, combined with purely algebraic technique (reduction of similar terms, factorization and so on), really simplify both forms of the obtained expressions (invariant, i.e. formulated in the dual space and covariant, i.e. formulated in the original 3D space).

In the appendix to the second part [119] a generalization of the spinors concept to represent translation (hyperspinors) is proposed. Thus Hestens is able to reduce the composition of arbitrary displacements to multiplications

^{viii}helical line does not need to lie within the body

and to obtain a universal description of evolution of a kinematic chain via both rotations and translations.

Forward Kinematics

You can't fall off the floor.

Murphy's Law

It is natural to consider forward kinematics methods together with procedural animation. The essence of these approaches is the hierarchical determination of the limb positions on the basis of given variations in time of the joints angles. In other words, they provide transformation of position and velocity from the joint space (joint angles) to Cartesian coordinates.

Forward kinematics approach provides a complete control of the motion at very low computational cost $O(n)$, where n is the number of the joints. Its advantage is the use of high level parameters (speed, step length etc.) that allows the animator to easily generate families of different motions.

There are two main drawbacks of these methods. Firstly, special handling is required to satisfy obvious constraints imposed on the motion (such as, for example, a feet contact with the surface during walking). In this example a popular solution to provide that the supporting foot would not go through or off the ground is to shift the root of the articulated figure to this foot. Secondly, it is quite animator's time consuming and needs considerable skill to get convincing motion and these requirements grow with increasing of the complexity of either the human model (number of DOFs) or the motion.

These approaches are mainly useful for the well known movements whose peculiarities are known from observations [54, 96, 313].

Inverse Kinematics

While in a classical keyframe approach an animator has to directly manipulate degrees of freedom of an object [159], application of the inverse kinematics methods allows one to indicate the position of specific points of the articulated figure (*end-effectors*) (such as a hand or foot) and let the computer to determine the values of the joints angles that provide the desired configuration [19, 96]. In other words, the end-effector position and orientation control all the joints along an articulated kinematic chain [150, 274, 315] thus reducing greatly the number of control parameters. It should be noted, however, that the reconstruction of the intermediate joints angles is not unique and, as was noted by Bernstein [31], the simplicity of the end-effector trajectory does not imply that those of the intermediate joints will be also simple (in fact, quite the opposite is observed).

Thus in addition to the movement of the end-effectors the animator should define a set of constraints that will drive the limbs in a unique way. Some of constraints (mainly of geometrical nature: feet position during locomotion, obstacle avoidance etc.) are obvious while the others could be used to influence the style of motion [41, 223].

A number of methods to implement inverse kinematics approaches has been proposed. Zhao & Badler [315] have given a detailed description of the non-linear programming algorithm that remains robust even for the articulated figures with a large number of joints. All spatial constraints are divided into those that applied to the figure itself and those that refer to the environment. Two approaches (the pseudo inverse method with explicit optimization and the extended Jacobian method) have been studied by Tevatia & Schaal [269]. The methods have been compared for the test case of a 10-DOF figure model. Results for a 30-DOF model have been tested on a humanoid robot. Miller et.al. [193] proposed to use the singular value decomposition method for solution of the underdetermined system of equations.

A variant of the inverse kinematics method called "differential inverse kinematics" is proposed by Chaffin et.al. [61]. The method is based on using velocities (rates) instead of positions.

Boulic & Thalmann [45] have demonstrated how one could combine direct and inverse kinematics: a "leg-correction" procedure is invoked if the foot penetrates the ground after forward kinematics computation and inverse kinematic algorithm is applied to modify the foot position. The complexity of inverse kinematic algorithm ($O(n^3)$ due to the need to invert the Jacobian matrix) is not a problem in this case since it is usually used for one leg only.

A possibility to extend the problem formulation and allow the animator to control not end-effectors only but in addition the centre of mass of the figure and moments of inertia has been studied by Baerlocher & Boulic [22]. The control of COM is needed, for example, to ensure the static balance of the complex articulated figure.

Integration of the mass distribution information to embody the position control of COM^{viii} of an articulated figure in the single support phase (open tree structure) in motion is studied in [44]. The method consists in evaluating the influence of the joints by relating instantaneous joints variations to the corresponding instantaneous translation of the total center of mass and a subsequent inversion of the resulting linear transformation in a way similar to inverse kinematics. The authors named the complete process Inverse *Kinetics* since it integrates mass distribution information. One of the advantages of the proposed approach over inverse kinematics is the greater convergence rate. The authors also considered a second order and first order inverse kinetics formulations.

2.3.2 Dynamics Approaches

All principles of gravity are negated by fear.

^{viii}The importance of the COM control confirm recent experimental study [221]. It has been shown that control of COM precedes all other changes when human has to change the direction of motion and followed by initiation of the head reorientation. Central nervous system uses two mechanisms to accomplish a turn: foot placement if planning can be made early and trunk roll motion (piking action about the hip joint in the frontal plane) otherwise to move COM towards the new direction.

The aim of dynamics-based animation is to provide plausible motion by accounting for the mechanical laws that govern figure's translation and rotation. These techniques can be divided into two basic categories: trajectory-based and controller-based [160]. The latter are discussed in detail in the next section.

Dynamic approaches can be used either for the correction of the existing motion (to generate more realistic motion by adding constraints) or for directly synthesizing the motion. These methods are based on applying the laws of mechanics to the articulated skeleton as an hierarchically ordered set of rigid bodies [24]. There are different approaches to implement (both direct and inverse) dynamics algorithms. One of them uses Lagrangian approach and generalized coordinates (each limb angular position is given in its parent's local coordinate system). In another one [27] the dynamics equations for each limb are solved independently and then additional forces that restore the joints constraints are computed.

Straightforward application of the inverse dynamics methods to closed kinematics chains is not possible. The difficulty stems from indeterminacy of the problem: for example, it is unclear how to distribute force and torque among the legs for an articulated figure in the double support phase. Ko & Badler [149] have suggested to divide the force in proportion to the distances between the projections of the center of mass and the ankles. This solution is, however, a static one and does not account for the dynamics of the motion. Oshita & Makinouchi [215] have extended this method by including into consideration the acceleration of the center of mass. Inverse dynamics methods could not also handle collisions [220].

One can combine kinematics and dynamics algorithms using the latter as a post-processing tool that restores the physical realism of the motion by satisfying corresponding constraints [148, 149]. It is possible to correct the results of inverse dynamics computations (if needed), as was done in the cited papers, to ensure balance and "comfort". The latter is interpreted by the authors as a limit on the maximum torque that can be exerted at a joint. If this condition is violated ("strength violation"), the joint trajectory is modified so as to reduce the torque. This approach is limited, however, since it is difficult to include some constraints (gravity effects for running or getting up, for example) [200]. Moreover, two-stage iterative computations do not guarantee a convergence.

Another example of coupling kinematics and dynamics computations can be found in Newman & Schaffner [204]. The authors studied an extravehicular activity via inverse kinematics to compute the motion of the system (satellite + astronaut) and then used these recorded motions to calculate the astronaut's body joint torques. A seven-segmented body model has been used to study movements in microgravity in [316].

Isaacs & Cohen [132] allowed a subset of the links in the figure to be controlled kinematically while the rest were computed using dynamics. A system of simultaneous dynamic equations has been assembled and the known accelerations

ations of the kinematics links have been factored out.

In the works of Armstrong et.al. [14] all the links have been controlled by the dynamics simulation, however, some have been selected for additional kinematic control via constraints. Four cases have been considered:

1. free link (no kinematic control)
2. fixed in space
3. fixed in relation to the parent joint
4. forced to match the position and orientation of the kinematic motion

A similar approach has been suggested by Westenhofer [293]. A notion of a *kinematic clone* is introduced as a link-for-link copy of the articulated figure that will be simulated dynamically. Connection between the figures is provided by the springs joining the corresponding links. Flexibility of the method could be achieved by tuning the springs' stiffness.

One of the critical issues in inverse dynamics simulation is the choice of the constraints or the goal function for the optimization problem. Li et.al. [172] have compared different optimization criteria in inverse dynamic optimization to predict antagonistic muscle forces and joint reaction forces during isokinetic flexion/extension and isometric extension exercises of the knee. Both quadriceps and hamstrings muscle groups have been included in this study. Four linear, nonlinear, and physiological optimization criteria have been considered. The authors have not reported significant differences in computed joint reaction forces and have suggested that the kinematic information involved in the inverse dynamic optimization is more important in prediction of the recruitment of the antagonistic muscles than the selection of a particular optimization criterion.

Spacetime constraints

It is a mistake to look too far ahead.

Winston Churchill

All the constraint-based approaches considered so far apply constraints to the individual instants in time to either compute the needed configurations to meet specified constraints (e.g. inverse kinematics), or the required forces to apply at the current instant to satisfy the constraints sometimes in the future (inverse dynamics). "Spacetime constraints" method introduced by Witkin & Kass [296] trying to compute the figure motion and time varying forces for the whole animation sequence instead of doing it sequentially frame by frame. To find the optimal motions, the constraints over the entire motion must be considered simultaneously. A placement of a constraint at the end of a motion can affect the behavior of a character at the beginning. At the same SIGGRAPH Conference a practically identical method called "Motion interpolation by optimal control" has been proposed by Brotman and Netravali^{ix}.

^{ix}it seems, however, that the first variant of the method is cited by far more frequently

While producing excellent results, spacetime methods are limited to the creation of relatively simple motions for the simple characters due to high computational cost $O(n^2m^2)$, where m is the number of the time steps.

Cohen [70] suggested to improve the situation by solving the optimization problem sequentially in "spacetime windows" defined as a sub-sets of degrees of freedom and sub-intervals of time.

A character simplification can be performed using three basic principles [229]:

DOF removal Some body parts are fused together by removing the DOFs linking them

Node subtree removal In some cases the entire subtree of the character hierarchy could be replaced with a single object (usually a mass point with three DOFs)

Symmetry movement Broad-jumps, for example, allows one to unite legs into one

Unfortunately, this procedure is hardly could be automated and made motion-independent.

A number of 2D applications have been computed in [208] using a genetic algorithm^x for the solution search.

A cardinal reduction of the computational complexity of the spacetime constraints methods can be achieved using the hierarchical representation of the optimization problem [177]. Another approach based on fast recursive dynamics formulation allowed the authors of [243] to simulate the motion of the human figure with 44 degrees of freedom. However, the known drawbacks of these methods (such as an approximate character of the physical laws satisfaction if the convergence is not attained, for example) remain.

2.3.3 Motion Controllers

Don't force it; get a large hammer.
Murphy's Law

It should be noted that the word "control" in the computer animation literature as well as in the present review is used in two different meanings:

1. an animator's ability to monitor and modify motion to meet one's requirements ("Animation is simulation plus control" – *John Platt*)
2. a process of maintaining balance and stability of the animated character's motion

^xsee details in the section **Optimization Methods**

The current meaning is usually quite clear from the context.

Advantages of the trajectory-based approaches are obvious: close resemblance to keyframing (the animator can control the end result), ability to find the most physically plausible motion even when no accurate solution exists. The drawback is that a new trajectory has to be generated for each new instance of the motion. The use of the motion controllers gives a number of advantages. Controller can be reusable, i.e. allowing to generate a number of motions with different initial states. There is a possibility to switch between the controllers during simulation or concatenate controllers to produce composite motions [16]. One of the greatest attractive features of this approach is an automatic synthesis of motion controllers. And last but not the least, controllers may be designed in such a way as to mimic some features of the human neuromusculo system [210] thus providing a hope for generation of motions that will be not anatomically only but physiologically (and perhaps psychologically) realistic as well, avoiding excessive torques, extraneous motions, rapid accelerations etc.

However, the problem of finding a control algorithm (i.e. to answer the question how to get from EVERY state of the system to EVERY other state) is more complex than of finding a particular trajectory that reaches a particular goal state from a particular start state. As a result, majority of studies of the optimal controllers have been focusing on the relatively simple systems.

A number of different approaches to control the motion have been proposed. One of the simplest ones is based on the use of finite state machines [123]. An algorithm determines what each joint should be doing at every phase of motion and ensures that the joints perform appropriate functions at appropriate times. Running, for example, is a cyclic activity that alternates between a stance phase, when one leg is providing support, and a flight phase, when neither foot is on the ground. During the stance phase, the ankle, knee and hip of the leg that is in contact with the ground must provide support and balance. When that leg is in the air, however, the hip has a different function—that of swinging the limb forward in preparation for the next touchdown. The state machine selects among the various roles of the hip and chooses the right action for the current phase of the running motion.

Associated with each phase are the control laws that compute the desired angles for each of the joints of the simulated human body. The control laws are the equations that represent how each body part should move to accomplish its intended function in each phase of the motion. To move the joints into the desired positions, the control system computes the appropriate torques with equations that act like springs, pulling the joints toward the desired angles. In essence, the equations are virtual muscles that move the various body parts into the right positions.

Closed loop controllers were developed by van de Panne et.al. [283] for the jumping "Luxo" lamp and other simple systems using dynamic programming.

For human figures with large number of degrees of freedom the search state is large. An approach using the fictitious external forces called by the authors

a "hand of God" (eliminated, if possible, or reduced at the late stages of the optimization) has been used in [284] to maintain the attitude of the walking human figure by shifting optimization procedure towards the desired solution. The problem with this approach is the incremental removal of the guiding forces.

A concept of the limiting cycle control to stabilize open-loop trajectories of the working human model with 19 DOFs has been used in [160, 161]. The fundamental entity used in this analysis is a "pose control graph" that is just a special type of the finite state machine. Each state in the pose control graph specifies a set of the desired joint angles for the figure with respect to some fixed reference position [160]. Joint angles are driven to their desired angles by joint actuator torques generated according to the proportional-derivative law. The main idea of the approach is to start with a passively unstable system, divide it into a number of cycles and stabilize each cycle in turn.

A new method for coordination of complex human motion that can be considered as a generalization of the finite state machine approach has been proposed by Multon et.al. [201]. Each motor unit is considered as an autonomous entity that includes two modules:

1. a black box that contains a model and its controller
2. a logic representation of the state of the system

Coordination model is subdivided into three levels with two-way information flow:

1. **the high level:** decomposes the task into the elementary actions
2. **the coordination level:** selects the motor units and provides synchronization
3. **the motor level:** executes the elementary actions

As an example the authors have simulated juggling with up to four balls.

A special kind of locomotion controllers can be generated by the evolutionary algorithms (see [247] and references therein) that are not directly applicable to a fixed figure locomotion since they are best for simultaneous evolution of the character locomotion skill and its morphology. However, this approach could produce non-trivial results: Hase & Yamazaki [113] have studied biped walking of humans using genetic algorithms allowing the shape of the body to adapt for the minimum energy consumption, muscular fatigue and skeletal load. A model consisting of 10 two-dimensional rigid links with 26 muscles and 18 neural oscillators evolved from a chimpanzee-shaped body to a human-like one. A variant of implementation of the evolutionary algorithm in an interactive frame has been described by Lim & Thalmann [175].

As it has been shown by Playter [225], passive dynamics can play a significant role in the motion stabilization reducing the need for the active control (a brief summary of the specific movements considered in the cited paper is given below in the section *Aerial movements*). It is also argued that delegating some

responsibility for the motion to the natural mechanical behavior of the body produces a natural-looking, coordinated movement in contrast to the non-linear control design approaches that inevitably rely upon the cancellation of some dynamics effects in order to get a solution and frequently result in a forced uncoordinated movement. Unfortunately, the author states, we do not know for sure if humans are using passive dynamics. A difficulty stems from the fact that both active control approach and open loop passive dynamic one could provide a similar dynamic response. For example, in aerial movements considered in [225], both techniques are based on using the arm tilt to control body twist.

However, Brenière et.al. [50] speculate that the differences between the gait initiation by children with under 200 days of walking experience and adults (in contrast to adults, who shift their centre of pressure toward the heels in anticipation of the start of the first step, infants do not use this strategy) are explained by the fact that children do not exploit the natural dynamics as adults do since they have not mastered their postural control yet.

Another argument in favor of the passive dynamics can be found in [85]. The authors show that in normal walking use of passive dynamics to control the swing trajectory is a mechanism that serves to minimize energy cost during locomotion, in addition to reducing the complexity of the neural control. In a reactive situation (e.g. a slip during walking) the energy cost may not be a major determinant of the locomotor activity as there is a need for quick corrective action under the threat of a fall. An unexpected mechanical perturbation was applied to the foot during walking. Video data were input into inverse dynamics routine to obtain the joint moment and mechanical power profiles and to partition the joint moments into the active and passive components. The nervous system still utilized the passive dynamics of the effector system: the active control of the hip and knee joints were increased but the magnitude of the hip extensor/knee flexor moment was invariant and equal to 1.6. The intralimb dynamics identified during these responses may serve to simplify the complexity of the active control by the nervous system.

The obvious advantage of the passive dynamic control is that it is not computationally extensive.

Pratt & Pratt [231] have exploited the natural dynamics for the control of a planar bipedal robot. The authors have exploited the passive swing leg and the compliant ankle limit to avoid the active control. Simulating 7 links robot they use a finite state machine (with 4 states: Support, Toe off, Swing and Straighten) for each leg and genetic algorithm to adjust parameters with the efficiency (defined as distance travelled divided by the total energy) as the goal function. Another feature non related to the passive dynamics should be mentioned: introducing a kneecap allows using a very simple controller (a constant torque is applied so that the knee pushes against the stop) to get rid of unstable behavior for the straight leg. In extension of this work [129] a radial basis function neural network has been used to capture nonlinearities not accounted for by the linear spring-damper model.

An alternative to forward dynamics computations based on using optimized

motion controllers is to increase similarity with the human locomotion and consider advanced models of neuromuscular systems. This approach encounters a number of difficulties from the poor knowledge of neuromuscular activity in the living being and uncertainty in parameters to the huge computational cost. Still, the first encouraging steps in this direction are made [84].

A multi-phase optimal control technique has been used to simulate a vertical jump [277, 276]. The musculoskeletal system has been described by a set of ordinary differential equations containing the equations of motion and the first-order equations of the excitation-contraction dynamics of the muscles. The optimal control problem could be reduced to the non-linear programming problem (that can be solved by the standard sequential quadratic programming algorithms). The model of the leg consists of three rigid bodies activated by nine muscle groups.

A number of papers describe the use of artificial neural nets for the control of locomotion. For example, a comparison between Multi-Layer Perceptrons (MLP), Radial Basis Functions (RBF) and Self-Organising Motor Maps has been performed in [186] for a spring-legged figure. It was shown that neurocontrollers based on both MLP and RBF are preferable. These controllers provide good generalization of the motion to running at untrained speeds and to running over uneven terrain.

An attempt to develop a biology-inspired hierarchical control structure is undertaken in [72]. Controllers composed of RBF learn the control required at each level of the hierarchy. A modified supervised learning algorithm is used for lower levels while a reinforcement learning approach is exploited for high level.

An hierarchical ("decoupled tree-structure") approach to the development of controllers for the legged robots have been exploited by Reichler & Delcomyn [237]. The method could be applied to the robots consisting of a series of branching chains (like legs or arms) connected to a single reference member that could be fixed or mobile. Chains themselves consist of a number of segments (limbs) connected via joints. The authors have also considered penalty-based and alternative methods to treat contacts.

Young et.al.[303] have argued that the superiority of the human motor control system over controllers developed for robots is in simplification of the motion commands at the expense of the motion accuracy. The authors have suggested two command simplification schemes based on the equilibrium-point hypothesis for the human motion control and tested them for handwriting generation example.

2.3.4 Animation of Deformable Objects

A cat will assume the shape of its container.
Cartoon Laws of Physics

The topic of this section is partly overlaps with that on the interpolation methods. It is necessary to mention a few examples of the unacceptable images generated by a "brute force" interpolation even based on the underlying

skeleton structure (*skeleton-subspace deformation*). This algorithm is present in the commercial software packages under different names such as skinning, enveloping etc. [171]. It is a variant of a more general approach developed by Magnenat-Thalmann et.al [183]. The position of a control point on the deforming surface of an object lies in the subspace defined by the rigid transformations of that point by the relevant skeletal coordinates. In such situations as shoulders and elbows deformations this subspace is too limited and no adjustment of the algorithm weights can produce acceptable results. The most common defect is a "collapsing joint" and examples of the partial and almost complete collapse of the elbow can be found in the cited paper. The authors introduce a new method ("pose space deformation") that generalizes and improves both shape interpolation and skeleton-driven deformation techniques.

A number of requirements to an advanced skeleton-based algorithm has been formulated by Lewis et.al. [171], two of which seem to be the most important:

- The algorithm should handle the general situation rather than treating each anatomical peculiarity as a special case
- The locality of deformation should be controllable in both Cartesian space and pose space (skeleton's configuration space)

Usually some variant of the multi-layered model considered first by Chadwick et al. [60] is used. These models contain a skeleton layer, intermediate layers which simulate the physical behavior of muscle, bone, fat tissue, etc., and a skin layer. Since the overall appearance of a human body is very much influenced by its internal muscle structures, the layered model is the most promising for realistic human animation. Sometimes it is stated that once the layered character is constructed, only the underlying skeleton needs to be animated while consistent shape deformations will be generated automatically [140, 270]. It should be noted, however, that this approach does not allow correct accounting for all effects related to the muscles properties (mass, inertia moments, volume).

Jianhua & Thalmann [135] describe an effective multi-layered approach for constructing and animating realistic human bodies using metaballs that are employed to simulate the gross behavior of bone, muscle, and fat tissue. The metaballs are attached to the proximal joints of the skeleton, arranged in an anatomically-based approximation. The skin surfaces are automatically constructed using cross-sectional sampling. Details of the procedure that provides efficient description of the deformations of a human limb by manipulating the cross-sectional contours may be found in [140]. It includes an heuristic element (one had to decide which contours should not be deformed) and thus requires a certain level of the animator's skill and understanding of human anatomy.

An extension of the free-form deformation model was suggested by Moccozet & Magnenat-Thalmann [197]. The authors enhanced this model using scattered data interpolation on Delaunay tessellation (Dirichlet/Voronoi diagrams). One of the advantages of the proposed method is a simple control of the local deformations. As an example, a multi-layer model is described where "Dirichlet

free-form deformation” model is used to simulate the intermediate layer between the skeleton and the skin for hand animation.

A use of B-splines for animation of physically-based deformable objects (first of all, muscles) is advocated by Ng-Thow-Hing & Fiume [207]. Applying a spring-mass model to the B-spline solid, the authors obtained a dynamic model. They also discussed a possibility to use nested B-splines to simulate a hierarchy of anatomical structures within the muscles.

A recent paper by Deunne et.al. [78] presents a method for animating deformable objects that use an automatic space and time adaptive level of detail technique and large-displacement strain tensor formulation. Continuous equations are solved by a local explicit finite element method. The method could be extended to treat deformation of bodies with topological changes, but, as the authors stress, this generalization is not trivial.

One of rather elaborate anatomically correct human models is being developed in Computer Graphics Lab, École Polytechnique Fédérale de Lausanne [39, 202, 203]. The aim of the authors is to attain fidelity not in skeleton modeling only, but in description of the body deformations as well. The model has three levels: the rigid body structure based on the data from a real skeleton, the muscle design and deformation based on physics concepts, and the skin generation. The skeleton model, in turn, has two levels. The first one consists of a topological tree structure with generic information about the joints, their degrees of freedom, their position, the limit angles of each articulation and so on. The second level is the bones that are attached to the joints for animation purposes. The global positions of the joints are defined based on the reconstructed three-dimensional skeleton while the limits of the joint angles are fixed from the observation of this skeleton animation^{xi}. The muscle representation is also organized in two levels. In the same way as the skeleton, one structure has been developed to represent the muscle actions and attachment to the bones and another one to simulate the muscle shape. The deformation has been described with the data coming from the muscle action structure and with the aid of a mass-spring model applied on the muscle surface. The physical model is based on the application of forces over all mass points that compose the mesh, generating new positions for them. Adding all the applied forces, the authors obtain a resultant force for each particle on the deformable mesh. Three different kinds of forces (elasticity, curvature and constraint force) have been considered. The current model is composed of 31 joints with 62 degrees of freedom, 73 bones, 33 muscles (represented by 105 fusiform muscle parts) and 186 action lines.

Methods used for simulation of the soft issues of the human body have been considered in detail in [187] (see also a monograph [189]). The author discusses uniaxial and multidimensional models that account for elastic or viscoelastic properties of the body parts and are either phenomenological or based on the detailed anatomical structure.

A biomechanical musculotendon model that reproduce force behavior ob-

^{xi}it should be noted that, strictly speaking, configurational spaces of joints could not be assumed independent

served in experiments has been developed by Ng Thow hing [206]. The model is sensitive to muscle and tendon lengths, muscle velocities and muscle activations. Deformation rules for generalized cylinders that govern their geometry changes in response to the underlying skeleton motion are defined.

Skin modeling

In those days the Rhinoceros's skin fitted him quite tight. There were no wrinkles in it anywhere.

Rudyard Kipling

Realistic human animation requires adequate description of the skin deformation, especially for the close-ups.

In the *elastic surface layer model* by Turnwer & Thalmann [279] the skin was simulated as an elastically deformable surface wrapped around an articulated figure. This surface was not attached to the underlying layers (such as muscles and fat) but allowed sliding freely. On the other hand, in [305] the skin points are fixed to the underlying bones and move with them. Evidently these two examples present extreme possibilities of skin deformation simulation.

A more justifiable approach is to relate the skin deformation to the contraction of the underlying muscles [268].

An impressive demonstration of skin animation is modeling of wrinkles evolution that accompanies hand movements [140, 302].

Hair Modeling

Would you want to do elastic bodies on each blade of grass?

Alan Barr

One of the most difficult issues in simulating believable human motion is description of the hair dynamics [110]. More exactly, the dynamics of *long* hair (hair-hair, hair-body and hair-air interaction) are extremely complex. A number of approaches have been reviewed in the cited paper. In the explicit hair models each hair strand is considered for shape and dynamics that makes them extremely computationally intensive. In [74, 244] a mass-spring-hinge model to control the position and orientation of the individual hair strand has been used. Another approach [12] used a simplified one-dimensional beam model. None of these studies treated hair-hair and hair-air interactions.

A novel approach to this challenging problem has been proposed recently by Hadap & Magnenat-Thalmann [111]. It combines a description of an individual hair as a serial rigid multibody chain and continuum description of the hair volume.

The treatment of the evolution of the hair volume by fluid mechanics methods allows the authors to consider not only hair-hair interactions but hair-air as well simulating the motion of the hair-air mixture.

2.3.5 Motion Planning

If you don't care where you are, you ain't lost.
Murphy's Law Book Two

Motion planning studies originate from robotics [165]. The problem can be stated in a classical formulation as finding a collision-free path for a rigid or articulated object among rigid static obstacles. Evidently it is relevant for a human motion animation as well with the only comment: one has also to avoid collisions among the limbs of an articulated figure.

Sometimes motion planning as a pure geometrical problem of computing a collision-free path among static obstacles is referred to as *path* planning [164].

Path Planning (Navigation)

I know a place round the corner here, where you can get a drop of the finest Scotch whisky you ever tasted – put you right in less than no time.
Jerome K. Jerome

To give a problem mathematical formulation a concept of figure's *configurational space* [179] is useful. A figure is represented as a point while configurational space encodes figure's DOFs. The obstacles in the Cartesian space are mapped into forbidden regions in the configuration space. Path planning is thus reduced to finding a point path in the space with blocked regions. Unfortunately, this space has as many dimensions as the figure has DOFs.

Huge computational resources needed for the implementation of the rigorous planners forced development of heuristic methods where, for example, a free space is represented by a collection of simple cells [52] or with the aid of potential field [26]. However, these approaches fail for path planning for a figure with more than 4 or 5 DOFs: a number of cells becomes too large or the potential field has local minima.

Probably the most robust planners for articulated figures with a large number of DOFs are those based on the statistical approach. A randomized planner described by Barraquand & Latombe [26] in addition to the steps towards the solution allows "random motions" to escape local minima^{xii}. A method based on random sampling the configurational space and connecting the samples in the free space by local paths, thus creating a *probabilistic roadmap* (PRM), is proposed by Kavraki et.al. [142].

PRM path planners work well if free space does not contain "narrow passages" [128]. Otherwise, they require a prohibitively large number of samples. Sometimes [126] it is recommended to accept the path if the penetration distance into the obstacle is small (in plain words, a hand can go into the wall if not too deep).

^{xii}evidently, an approach identical to simulated annealing is used.

Schöner et.al. [251, 252] have developed a dynamical system for robot planning. A set of the behavioral variables (such as heading direction and velocity) define a state space. Path planning is governed by a nonlinear dynamical system for the behavioral variables. Constraints (target following, obstacle avoidance etc) are modelled as the forces that define attractors and "repellers" for the system. Individual constraints contributions are weighted with weights determined by the second dynamical system ("task level system") that has a characteristic time scale smaller than that of the "movement level system" [158].

Collision Avoidance

Any body passing through solid matter will leave a perforation conforming to its perimeter.

Cartoon Laws of Physics

A naive algorithm for the collision checking (to consider every pair of faces or edges in the object representation) will require $O(n^2)$ operations and clearly unacceptable for complex articulated figures. More intelligent approaches should use the properties of the objects (or their surfaces) and/or some general space search algorithms that account for the object location such as hashing, for example. These methods could be classified as *feature-based* [196] and *hierarchical* [147]. The former one exploits the spatial coherence in the geometry model while the latter pre-computes a hierarchy of bounding volumes for each object. Hierarchies using different primitive forms have been considered. For example, spheres are good for a broad class of objects [216]. These ideas, of course, could be combined in a single method.

An algorithm for the self-collision detection of discretized polygonal surfaces has been suggested in [287]. The efficiency of the method stems from two essential issues: 1) the surface is assumed to be regular (smooth) that allows the authors to exclude a large number of collision tests; 2) a hierarchical representation of the surface is used.

A study of cooperative motion between the arms has been performed in [150]. The authors rely heavily on the neurophysiology results that state that the arms movements are primarily defined kinematically. Thus Koga et.al do not consider dynamics and muscle models but use inverse kinematics approach in the development of the motion planner.

A generalization of the probabilistic roadmap planner to the case of moving objects has been proposed recently in [127]. The algorithm is based on sampling the figure's free space with subsequent integration of the equations and can provide satisfaction of both kinematic and dynamic constraints.

An efficient algorithm of the collision avoidance should be built on the efficient kinematic data structure. Halperin et.al. [112] called this problem *dynamic maintenance of kinematic structures*. Given a set of rigid bodies linked together by kinematics constraints (an articulated figure) that moves in 3D space, the aim is to efficiently maintain a data structure that would allow one to quickly answer the range queries as the bodies change their position. A query usually

specifies a region in space and asks whether the figure intersects this region or lies within a certain distance from it. The data structure is then used to select a small subset of the bodies to which exact intersection/distance algorithms will be applied. An initial construction of such a data structure is a relatively simple problem for a given values of the joints angles compared to the problem of updating this structure when the joint parameters change. The authors studied approaches that use balance decomposition of the tree presenting a figure and got some formal estimates of the complexity of the problem.

2.3.6 Autonomous Character Behavior

In real life it takes only one to make a quarrel.
Ogden Nash

One can distinguish two types of autonomous characters: *agents* and *avatars* [20]. An agent is a virtual human figure representation that is created and controlled by a computer code. An avatar is a virtual human controlled by a live participant. A Smart Avatar [256] should understand what the human tells it to do. It requires the development of a conceptual representation of actions, objects, and agents which is simultaneously suitable for execution (simulation) as well as for natural language expression. A successful implementation of such architecture called Parameterized Action Representation is reported by Badler et.al. [21].

Another important advancement made in the cited paper is the implementation of a non-linear animation model via simulated parallelism. A parallel virtual machine is called Parallel Transition Network (PaT-Net). Network nodes represent processes and links contain predicates, conditions, rules, or other functions that cause transitions to other process nodes. Synchronization across processes or networks is effected through message-passing or global variable blackboards. The key feature of PaT-Nets is their conditional structure. Traditional animation tools use linear time-lines on which actions are placed and ordered. A PaT-Net provides a non-linear animation model, since movements can be triggered, modified, or stopped by transition to other nodes. This is important for autonomous behavior since conditional execution enables reactivity and decision-making capabilities which one would like to find in an animated character.

The common approach to the behavior of the autonomous character is a multi-level one. These levels may be called differently and defined in different words but the essence of this structure is invariant. For example, Blumberg & Galyean [37] suggested a three layer hierarchy: *motivation*, *task*, and *motor* while in [238] these layers are named as *action selection*, *steering*, and *locomotion*. These "steering behaviors" are largely independent on the details the character's means of locomotion. Their combinations can be used to achieve the higher level goals. One can list such steering behaviors as pursuit, evasion, quarry, obstacle avoidance, wander, separation, alignment etc. [238].

Blumberg & Galyean [37] also state that autonomous character still should be under some external control (called "directability"). They suggest three levels of such control in accordance with three levels of behavior. The imperative forms of the directions are defined as:

1. Suggest how an action should be performed if the Behavior System is wishing to perform this action
2. Do it, if the Behavior System does not object
3. Do it, independent of the Behavior System

A system for control of behavior of agents described in [102] uses both a model of continuous behavior and a discrete scheduling mechanism for changing the behavior in time.

Goldstein et.al. [100] have used a dynamic system approach to generation low-level behavior of autonomous agents similar to one exploited by Schönner et.al. [251, 252]. The authors have derived a set of ordinary differential equations that govern time variation of the heading direction and speed of the agent. They simulated such behaviors as obstacle avoidance and target tracking in two dimensions. The appealing feature of the algorithm is the linear dependence of the number of operations on the number of obstacles.

A knowledge-based system for the agents behavior in the both "simple" virtual world and in real world has been developed by Funge [93]. The models that able to exhibit low-level autonomous behavior (such as an obstacle avoidance) are called by the author *behavior* ones while for high-level behavior (a pursuit or evasion) he reserves the term *cognitive* models. One of the main difficulties of following this approach is an appropriate knowledge representation. The core of the designed by the author autonomous "mermaids" and "mermen" consists of the reactive system and reasoning engine.

An architecture for behavioral human locomotion has been developed by Reich [236]. It includes three main parts: state machine, behaviors and locomotion engine. A number of behaviors has been implemented either via the locomotion engine or the state-machine layer such as avoidance, ducking, turning, chasing, terrain awareness etc.

2.3.7 Optimization methods

At the rate you are learning, it would take more than two hundred years to teach it to you.

Robert Asprin

The most computationally intensive part of physically-based animation is by all means the optimization problem for inverse based approaches (and almost every animation tool includes some kind of the inverse kinematics solver) or learning (training) for the controller-based methods.

A number of methods have been exploiting in animation from the classical ones such as, for example, gradient-based optimization or non-linear programming to relatively new ones originating mainly from artificial intelligence and artificial life studies (neural nets, fuzzy logic, evolutionary algorithms).

A trust region method (approximation of the goal function with a quadratic function in the neighborhood of the current estimate) allowed the authors of [280] to solve a rather large optimization problem with about 4000 parameters. This paper is also of interest as an example of using adaptive B-spline wavelet to represent joints trajectory.

One of the difficulties of the optimization problem in the animation context is the redundancy of the basic system (in other words, the system is underactuated [262]: the number of degrees of freedom of the articulated figure can be much greater than the number of the end-effectors the animator is monitoring). Frequently the optimization process is got trapped in the local minimum. In such cases optimization methods that include some stochastic element work best.

Stochastic Gradient Ascent (SGA) has been used successfully to search for locally optimal controllers for character animation in [282]. The authors established an interesting gait by randomly generating weights for the sensor-actuator network, and then using SGA to optimize parameters which affect the quality, but not the type, of the gait. Specifically, SGA perturbs a random parameter of the controller, and keeps the new controller if the character's motion gets better. A gait improved if it moved forward faster, or if the character's body had an upright posture.

SGA has a major drawback. It depends heavily on the initial guess given for the controller. If you start with a poor guess for the controller, you might not find an acceptable solution (you get stuck in a local maximum). Such situation is often observed when SGA is used for spacetime constraints or forward methods. This is typical for other methods of searching for a local optimum not covered here - they depend on an initial guess being near the global optimum in order to find it.

Simulated annealing is designed to overcome this problem, by allowing the parameters to be varied randomly some of the time, thereby escaping local maxima. This technique is used to search for a globally optimal solution. It is similar to SGA, but uses a temperature parameter to determine the probability that a change of a parameter will be allowed to worsen the optimization. As a result, it will accept some intermediate steps which worsen the controller, while allowing the controller to get better eventually. It has been also used in [282] to fine-tune controllers, and has been found to perform competitively with SGA, converging to a solution a bit faster or slower, depending on the particular problem situation.

Both SGA and simulated annealing have some drawbacks in common. They depend on a control system model with a fixed set of parameters to optimize - in [208] there are 10 stimulus-response pairs, and in [282] the topology of the control network is fixed: only its parameters change. The choice of these parameters is critical, and will decide whether the problem is soluble at all. The

parameterizations used in these two papers are extremely rich, allowing for a wide variety of controllers.

Genetic Algorithms (GAs) [99] are the methods modelled on a natural process which provides adaptation: evolution. GAs have been used to solve the problems of producing robust controllers and globally optimal controllers found in other approaches to physically-based character animation. The reason GAs work is that they belong to a class of a global search technique. The initial population takes a random sample of the search space, usually limited to relatively simple controllers. Mutation and sexual cross-over ensure that more complex controllers are explored as well, often in widely different parts of the search space. The search is also guided by human creativity through the choice of fitness functions to produce more interesting and acceptable results.

It is very hard to specify the torques around the joints so that a character behaves the way the animator wants. Torque is not a natural way for an animator to specify the motion of a figure. The number of degrees of freedom of an articulated character grows very rapidly with its complexity, and it becomes correspondingly harder to specify its controls. Even with simple two or three link characters, GAs have found some motions which were not anticipated by the authors [208].

With GAs, the search space does not have to be limited. GAs can combine the sensors, internal nodes and effectors in a control system in arbitrary ways, to generate controllers of very different forms than might be designed by hand.

A variable fitness function is also useful for the design of robust controllers. Gritz [107, 108, 106] uses a function which starts with a main goal (reach point X at the end of the time allotment) and gradually adds additional style points for completing the motion early, penalties for falling over or hitting its head, etc. This allows the main goal to evolve individuals which are then refined by the style restrictions. Additionally, fitness is averaged over multiple tries with different end-target points, resulting in controllers which could move any distance and stop.

However, GAs often do not converge to useful results without some tweaking. In [208] the controller for a bipedal figure was evaluated on the basis of the forward motion of the center of mass. The population of controllers converged very quickly to the strategy of falling forwards, and was unable to evolve to a more interesting strategy. When the evaluation metric was changed to the forward motion of the point between the figure's feet, the GA produced more interesting walking/hopping motions.

In this way GAs are similar to other numerical techniques. SGA is designed only to find a local optimum, and simulated annealing was designed to address this shortcoming. Because of their large populations and variety of genetic material available for solution of the problem, GAs are more suited for global optimization than SGA. But because they are probabilistic, results from two otherwise identical runs can be quite different, and we are not guaranteed to find a solution, where SGA will at least find a locally optimal solution. Gritz [108, 106] showed one way to deal with this problem, by starting the population with

an easier fitness function and gradually adding style restrictions. An alternative that does not use GAs (a "hand of God") has already been mentioned in section *Motion controllers*.

2.4 Motion Editing

2.4.1 Processing of Captured Motion

In order to use videocaptured motion for editing/modification/personification one has to process it. Deriving human body shape and motion from optical or magnetic motion-capture data is an inherently difficult task. The body is very complex and the data are rarely error-free and often incomplete. The task becomes even more difficult if one attempts to use much noisier video-data instead.

There are two main approaches for human motion analysis: motion analysis involving human body parts and tracking of motion [2]. The aim of tracking, using either single or multiple camera, is to establish correspondence of the image structure between the consecutive frames. Generally, the features to be tracked can be chosen rather arbitrary [3] trading accuracy for efficiency. Since human motion is essentially the movement of supporting bones, it is evident that analysis mode not naturally tied to the human figure structure could not be considered an element of the physically based animation system.

One can distinguish two strategies of the human motion analysis that explicitly exploit human body structure depending on whether a priori information about an object's shape is used or not. These approaches are referred to as model-based and non-model based, respectively [2]. Both include as the main elements feature extraction and feature correspondence, the difference being manifested itself in the process of establishing feature correspondence between consecutive frames. Examples of non-model based motion analysis using different heuristic assumptions have been briefly reviewed by Aggarwal & Cai in the cited paper.

However, model based analysis is by all means the most promising approach for the processing videocaptured motion intended for subsequent physically based editing. One can use stick figures, 2D contours or volumetric models. Chen & Lee [63] used the model with 17 segments and 14 joints (neck, pelvis, shoulder, elbow, wrist, hip, knee, ankle) that has been fitted to captured 2D projections. Similar approach was exploited in [33] to model the lower limbs of the human body. Both papers deal mainly with the gait analysis. An attempt to describe the human motion solely on the basis of the outline of the human figure was made in [170].

In a number of papers different volumetric models have been used to analyze the human motion. For example, in the model used in [124], [242] 14 elliptic cylinders have been considered to approximate a human figure in analysis of walking. In the model [214] consisting of 24 rigid segments and 25 joints the surface of each segment was defined as a union of overlapping spheres. This

early model already included restrictions on the joint angles and the detection of collisions between the non-adjacent segments.

In all mentioned methods the complexity of matching the image to the human body model is determined by the number of model parameters. Evidently, fitting of the image features to the model is simpler for the models with few parameters (such as a stick figure model), however, extracting these features can be more difficult and needs care [2].

A novel approach for translating the human motion from captured image sequences to computer animations in real time has been proposed in [212]. A motion generator analyzes the current human motion and/or posture from data obtained by processing the source video images, and then generates a set of the joint angles for the target human body model. The authors claim that compared with conventional motion capture methods, this approach is more robust, and tolerant to the broader environmental and postural conditions.

In [224] a framework for 3D shape and motion recovery of articulated deformable objects is developed. The authors propose a formal procedure that incorporates the use of implicit surfaces into earlier robotics approaches that were designed to handle articulated structures. They demonstrate its effectiveness for human body modeling from video sequences.

A system for tracking a 3D person motion that is able tolerate full (temporary) occlusions is described in [301]. The system uses an extended Kalman filter for probabilistic integration of 2D inputs from two or more cameras into a dynamic 3D skeletal model. Another approach to motion tracking that allows occlusion of body parts is described in [304]. the method is based on learning the temporal-flow models using principal component analysis.

An anatomically based converter for human motion capture has been described by Molet et.al. [198]. The method is based on the calibration of both hierarchical model of the human skeleton and sensors. One of the important element of the procedure is the transformation matrix between the sensor frame and virtual joint frame.

A closely related question of storing the produced motion has been studied in [103]. The authors compare a number of production/playback methods:

1. generating and rendering the motion of characters completely off-line
2. the same as the previous, but storing 3D snapshots
3. storing the full motion in posture graphs

The first method (storing 2D snapshot) is the fastest but extremely inflexible. If the motion is to be used in 3D scene, one has to store different 2D snapshots for different view angles (for example, in DOOM eight views have been recorded [245]). This last drawback is removed in the second method that still remains a rather inflexible approach.

The authors advocate the last one since it stores not the *results* of the motions (images) but the *motions* themselves (joint angles between articulated figures).

Thus the motion can be easily modified. Another advantage of this approach is the seamless incorporation of the possibility to generate motions of simpler articulated figures. This process called by the authors "slaving" allows one to use for rendering higher resolution models when they are close to the viewpoint and lower resolution ones when far away. The authors used three such models with different level-of-detail (LOD): "human-high" (73 joints, 134 DOFs), "human-med" (17 joints, 50 DOFs), and "human-low" (11 joints, 21 DOFs).

2.4.2 Editing Methods

Take care to get what you like or you will be forced to like what you get.

George Bernard Shaw

Motion editing can be performed in several ways. The simplest one is probably parameterization that hopefully will allow one to retarget the motion to another character and/or environment. However, it should be done with care so as not to violate the motion constraints and not to get such unpleasant artifacts as ground penetration or feet sliding on the surface. The problems arise when the captured (or previously generated) motions have to be adjusted to environments different from those in which they have been obtained. Rough terrain and collisions are the two examples of such potentially dangerous transformations.

Perhaps one of the most trivial editing methods is "motion synthesis by example" [157]. The technique is based on choosing the "best fitting" sample from the set of representative example motions and creating the new animations by cutting-and-pasting together automatically tailored fragments.

One of the the most popular methods for motion editing (more exactly, motion blending or mixing) is interpolation. Interpolation is used widely for generating inbetweens during keyframing and for transformation of the graphical objects (morphing). Usually morphing is implemented as image-based technique [298]. A more advanced object-space morphing is based on explicit representation of the objects (as a rule, either polygons or polyhedra) [105]. One of the major phases of the algorithm is establishing of a correspondence between the geometric features (*vertex correspondence problem*). A new interpolation method that blends the interiors of the geometric objects rather than their boundaries has been proposed recently by Alexa et.al. [6]. As the name of this method ("as-rigid-as-possible shape interpolation") indicates the aim of the authors is to design a method that would introduce no excessive global or local deformations.

Motion blending can be performed not in the Cartesian space and time only but in the frequency domain as well. In the latter case the trajectories undergo one of the signal processing procedures (it can be, for example, Fourier transform [281] or multiresolution filtering [56, 95],). One variant of this approach is called "motion warping" [297].

Comparing Fourier analysis and multiresolution filtering, the latter is doubtlessly more attractive for the non-periodic signal of the finite duration. On the other

hand, for cyclic motions such as walking, which are quasi-periodic, Fourier transform could be an adequate analysis tool.

The main shortcoming of the geometric interpolation comes from independent processing of key figure points that can result in such artifacts as extremities shortening.

A better way is to interpolate not a set of figure points but the joints trajectories. However, since it is done independently, errors^{xiii} can be generated: there is a strong coupling between joints trajectories.

Still, such methods are used up to the present time. Will & Hahn [295] developed an interpolated synthesis of motion as a tool for producing a continuum space of possible motions from a small set of examples (that can come from keyframing, motion capture or physically-based simulations). The authors suggested a hybrid position and orientation of the skeleton. This hybrid representation does not ensure constant limb length, but the authors argue that this drawback can be cured by a post-processing step of conversion to fixed limb lengths. To reduce the search time for scattered raw data it is proposed to perform a pre-processing step of filling a regular grid of the parameter space. Linear interpolation is done for the vector position components (or cubic spline interpolation in the cylindrical coordinate system) while spherical linear interpolation is used for each quaternion orientation component. A number of examples presented in [295] illustrate the robustness of the algorithm. However, as the authors note, the interpolation synthesis is limited to small number of parameters, on the order of ten (in fact all the examples demonstrated involved from one to three parameters).

A method called "shape and animation by example" is described by Sloan et.al. [259]. Its distinctive feature is the possibility to extrapolate between the multiple forms and motions. One of the precedents of this method is an algorithm for multiple blending based on the implicit function presentation of shapes [278]. The method of [259] can generate a continuum range of forms (*shapes*) and motions (*verbs*). The examples to be used for blending should have the same structure and the same number of degrees of freedom. Since all forms in shape must have the same topological structure (the same number of nodes with the same connectivity), the problem of correspondence between the entities is avoided. A combination of the radial basis functions and low order polynomials is used to perform interpolation of scattered data. The efficiency of algorithm stems from the fact that one set of linear basis and one set of radial basis per *example* are needed and usually the number of examples is considerably less than the number of DOFs. Sometimes the results of interpolation, however, are not acceptable (such as a muscle bulging or skin shrinking near a the rotation point) and the authors suggested the algorithms for manual tuning the process (in particular, by introducing additional *pseudo-examples*).

Recently Brand & Hertzmann [46] proposed an approach to the motion editing based exclusively on the learning problem. There is no kinematic or

^{xiii}in addition to the "static" artifacts such as "collapsing joint" discussed early in the section *Animation of the deformable objects*

dynamic problem, no underlying figure structure. All the information is extracted from the processed example motions and the basic motion ("structure") and secondary motions ("style") are obtained. The author use a probabilistic finite-state machine (hidden Markov model) called *style machine*. Some cases of human locomotion are presented. It should be noted, however, that this approach is limited and hardly can perform well when transition of the human cyclic motion to the rest occurs: neither the geometrical nor inertial properties of the human figure that should be crucial in such transition motion could be learned by presented algorithm. An evident extension of the method is incorporation of the incremental learning algorithms.

Articulated figure motion editing can be accomplished by the combined use of direct and inverse kinematic control [45] already mentioned in the section on kinematics approaches. Applying this procedure to an existing motion allows the animator to specify goal-oriented modifications. The main idea is to consider a desired joint space motion as a reference model used in a secondary task of the inverse kinematics control scheme. This approach provides generalization of the joint-space-based motions to a larger set of articulated figures. The process of editing can be also formulated in terms of the COACH-TRAINEE paradigm [40] designed primarily as a tool for adding physical realism to predefined motions via additional constraints: the aim is to retain most of the kinematics of the initial motion (COACH) in the process of satisfying a number of geometrical constraints to produce a new motion (TRAINEE).

Recently Gleicher [97] has made a comparison of a number of the constraint-based motion editing methods. These methods explicitly represent certain features of the motion that are to be preserved or changed in a controllable way. In this aspect the constraint-based methods differ from other methods such as pure signal processing approaches [281, 56, 297].

The most effective treatment of the temporal constraints is based on the observation that high frequencies in motion are almost always noticeable and thus must be reserved during editing [297, 98].

It should be noted that the constraint-based motion editing methods could not be applied to editing *per se* but as a correction procedure (for example, to restore constraints after they have been violated by the signal processing operation).

Gleicher suggested the following taxonomy for these methods based on their approach to handling temporal constraints:

- **Per-Key Methods.** In this case the temporal continuity between the poses is provided by interpolation. The author calls such methods *per-key inverse kinematics*. The main difficulty of this approach is to get a set of sparse well-chosen key frames to represent the motion.
- **Motion Warping or Displacement Mapping.** In these methods [56, 297] the changes to the motion are keyframed. This approach is called *motion warping plus inverse kinematics*.

- **Per-Frame Methods.** These methods can be considered as a special case of the per-key methods where the keys are regularly spaced.
- **Per-Frame Plus Filtering.** The author argues that the last method is the best among the considered ones. The first example of this approach has been reported by Lee & Shin [168] as the "Hierarchical motion editing technique" that used B-spline fitting to implement low-pass filtering.
- **Spacetime Methods.** In contrast to all the previous methods frames are not considered individually in this approach. The solver computes an entire motion (or a sub-window of it) Unfortunately, a constrained optimization problem turns out to be very large.
- **Physical Approaches.** In the methods considered so far most of physical properties have been neglected (including Newton's laws) for the sake of performance: kinetic constraints and energy properties are particularly computationally expensive in the spacetime framework (that is easy to understand since such constraints produce *coupling* between frames). However, in some cases it is impossible to discard the laws of mechanics if one wants to get a realistic motion [230].

Modifying human motion capture data using dynamic simulation has been studied by Zordan & Hodgins [317]. A number of new features added by the authors: a (limited) collision handler, specialized task controllers to edit a character motion at the behavior level, and task controllers that allow animation of DOFs that had not been captured (for example, animation of the whole body with only upper part captured using a special controller on lower part). Captured data are converted to the joint angles and used as the desired values for the tracking controller. The low-level control torques at each joint are computed using proportional-derivative controller that acts as a muscle model.

In [228] dynamics-based editing of the captured data is considered as dynamic filtering that can be used to maintain physical constraints. A novel element in this paper is an extension of the technique to treat friction-based contact of the character with environment.

An advanced editing method based on the spacetime constraints proposed in [151]. The most appealing feature of this approach is accounting for the muscle properties. The usual three-component Hill's model is used along with the model that describes the fatigue of muscles. The key feature of the computational procedure is a quantitative analysis of the (perhaps physiologically implausible) motion:

- the given trajectories are approximated by C^2 continuous functions (for example, by B-splines) and differentiated to get velocities and accelerations
- the joint torques are computed via inverse dynamics
- the joints torques are decomposed to the muskulotendon force

- check is performed for every muscle for the entire motion whether the muscle force is less than the maximum force that is exerable by the muscle

The motion transformation is performed in such a way as to reduce to zero the "infeasibility" function that measures the extent of the limiting force violation.

Oshita & Makinouchi [215] have proposed a dynamics-based method for tracking and modification of the captured motion. A kinematic motion sequence is used as an input. In contrast to the majority of other authors, Oshita & Makinouchi do not consider dynamic simulation as an aid to "cure" the unrealistic kinematic motion. They rather assume that the input motion is already realistic and consider dynamic filtering as means to adjust the motion to the changing environment. Primary (human strength model) and secondary constraints (accelerations of the center of mass and of end-effectors) are incorporated. As an example, an effect of the load in the hand on the motion of 39-DOFs figure is simulated.

Grassia [104] has developed a knowledge-based approach to the motion transformations. The knowledge takes the form of descriptive annotations on the example motions and rules that define how to combine/modify these motions. The suggested approach contains three main elements:

1. motion transformation methods (space warping, time warping etc.)
2. motion models (domain-specific rules, invariants, high-level parameters)
3. algorithms for combining motions

Lee [167] has developed some tools for motion editing based on the hierarchical approach and multiresolution. In particularity, general method of construction of spatial filters for smoothing orientation data and hierarchical curve fitting are considered. A multiresolution analysis of motion used to decompose the motion into the base one and stylistic features.

2.4.3 Personification

There is another: why may not that be the skull of a lawyer?
William Shakespeare

The amazing thing about human motion is that almost every human has its own unique style of, for example, walking that can be recognized from a large distance. The same (perhaps to a lesser extent) is true for static postures.

One of the essential aims of animation is to provide the character with individuality. Leaving aside such attributes as face, hair and clothing, one has a few ways for personification of the character and its motion:

- static biological structure (limbs lengths, muscle parameters)
- dynamic motion individuality directly connected to the muskuloskeletal system

- additional anthropometric and physiological parameters that can differ for the characters with the same external (static) appearance: "comfortable" limiting values of the joints angles, dynamic muscle parameters, parameters or functions that can account for the emotional state of the character or the level of fatigue etc.
- specific "secondary" movements that can be superimposed on the (almost any) basic motion
- motor skill that can be modified during the character life depending on her/his experience

An example of the adapting a specific motion (running and bicycling) to a new character can be found in [122]. The characters with different limb lengths, masses, and moments of inertia are considered. It is stressed that simple geometric scaling is not adequate since, for example, a man and a child differ not only in height but also in proportion (a child has heavier torso and shorter arms and legs).

The algorithm proposed by Hodgins & Pollard has two stages. First, an approximation to the new control system is obtained by scaling based on the sizes, masses, and moments of inertia of the new and old models. Second, a search process is used to tune the new control system. Since search space for the problem contains a lot of local minima, the authors used simulated annealing.

A development of this approach for scaling of the motion was suggested by Pollard in the later papers [226, 227]. To achieve fast performance, she decided to give up complete physical realism. The task is defined by specifying the reference motion (joint angles and root position in time), character description (joint locations, degrees of freedom and physical parameters) and user-defined adjustments (new character description, new speed etc.).

The algorithm consists of three steps: fitting of a simple task model to the reference motion data; scaling of both the reference motion and the simple machine version of this motion; correction of the scaled reference motion so it matches the scaled motion of the simple machine. The last step – mapping the motion back to the complete character – is performed using inverse kinematics at each frame of animation.

The task model for running used by the author consists of a point mass connected to feet by massless springs. It seems that the most dangerous part of the algorithm is the need to differentiate twice (!) the motion curves for the character centre of mass extracted from the reference motion to obtain accelerations – it is well known that numerical differentiation of the noisy data is a highly unstable process prone to errors.

An interesting mechanism to introduce individuality into the locomotion style has been proposed recently in [267]. The authors developed a corrective procedure that converts an unbalance motion into a balance one while preserving as much of the original motion as possible. The method is based on the monitoring and modification of the trajectory of the zero moment point. As

by-products of this approach two possibilities to personify motion appear. The balancing style of the moving human can be changed either by the variation of the size of foot sole or by tuning the joint's stiffness (and thus forcing a model to use waist joint and torso joints differently).

A "physiological" retargetting can be accomplished in the frame of musculoskeletal human model by Komura et.al. discussed above. An animator gets two possibilities to tune the physical ability of the character.

- by changing the length and the physiological cross-sectional area (PCSA)– we should refer to this approach as to *static* muscle tuning
- by changing the intracellular pH level as the measure of fatigue – we should refer to this approach as to *dynamic* muscle tuning

One can also, of course, increase the PCSA for the certain muscles as a result of the training or to reduce the limiting force due to the injury.

2.5 Analysis and Simulation of Specific Motions

Among terrestrial animals some fly, others move overground either by walking or crawling; aquatic animals either swim or walk. Quadrupeds and myriapods move with diagonal gaits. The lion and the camel amble.

Aristotle

One can name a few classes of human movements such as

- Posture changes and balance adjustments
- Reaching (and other arm gestures)
- Grasping (and other hand gestures)
- Locomotion (stepping, walking, running, climbing)
- Looking (and other head gestures)
- Physical force- or torque-induced movements (jumping, falling) etc.

It should be noted that, as a rule, more energetic motions are simpler for simulation: the dynamics of model constrain the motion and limit the space that must be searched for control laws for the natural-looking motion [123]. For example, it is easier to control running than reaching, and in turn the gymnast's vaulting is simpler than running in this context: while the gymnast is airborne greater part of the maneuver duration (control algorithm can influence the internal motion of the joints only), the runner is considerable part of time

in the contact with the ground and the computed joint torques directly control human motion as a whole.

The most studied specific human motion is, by obvious reasons, locomotion (walking and running). Bipedal locomotion is a topic of interest in computer animation, robotics and biomechanics.

2.5.1 Terrestrial Locomotion

Different modes of bipeds and quadrupeds locomotion are analyzed in [194]. It is shown, in particularity, that the popular pendulum and inverted pendulum models often used to study biped gait are limited from the mechanical point of view. In an ideal pendulum total conversion between potential and kinetic energies occur ("energy conversion parameter" is equal to 1) while in walking humans the value of this parameter is about 0.6). Energetics of human locomotion is usually discussed in terms of the metabolic energy required for motion that is determined experimentally via oxygen consumption^{xiv xv}. The dependence of the metabolic cost on the speed allows one to determine the transition from walk to run as a speed at which the latter becomes more economical^{xvi}.

Walking

- 1 lb. beefsteak, with
- 1 pt. bitter bear every six hours.
- 1 ten-mile walk every morning.

Jerome K. Jerome

The human gait is a complex multijoint movement that requires the coordination of many muscles. It is usually assumed that uniarticular muscles generate the propulsive energy while biarticular muscles provide the fine-tuned coordination. Walking can be called "controlled falling." Every time one takes a step, she/he leans forward and falls, and is caught by the outstretched foot. After her/his foot touches the ground, the body's weight is transferred to it and the knee bends to absorb the shock. All the body's limbs, not only feet and hips, but spine, arms, shoulders, and head as well, are moving to maintain balance. The decomposition of walking to the simpler movements of different joints has been described by Maestri [182]:

- The feet and legs – they propel the body forward.
- The hips, spine, and shoulders – the body's center of gravity is at the hips; all balance starts there, as does the rest of the body's motion. Hips'

^{xiv}strictly speaking, one should consider both aerobic and anaerobic energy sources [59]

^{xv}A direct mechanical calculation of the metabolic muscle activity has been used by Minetti & Alexander [195]

^{xvi}It is interesting to note that transition speeds between the gaits are different in acceleration and deceleration: "gait transition hysteresis" is observed [194].

movement can be considered as the two separate, overlapping rotations transmitted through the spine to the shoulders, which mirror the hips to maintain balance.

- The arms – unless the character is holding something or gesturing, its arms hang loose at the sides. When walking, they act like pendulums.
- The head and spine from the side – the spine absorbs some of the shock transmitted to the hips from the legs, making it flex from front to back a bit. In a standard walk, the head tries to stay level, with the eyes pointing in the direction of the walk, but it oscillates slightly to stay balanced.

It should be stressed that in addition to the forward motion in the sagittal plane a walking human oscillates in the frontal plane. During a step the body's centre of mass remains medial to the supporting foot and thus the body is unstable and is falling sideways. It has been suggested that this motion is controlled in a ballistic manner by proper setting of the initial (toe-off) position and velocity of the centre of mass [181].

The complexity of movement is also related to the fact that a particular muscle can accelerate many joints and segments, even the joints it does not span and segments to which it does not attach. A biarticular muscle can even act to accelerate one of the joints it spans opposite to its anatomical classification. For example, gastrocnemius may act to accelerate the knee into extension during upright standing [308].

It should be stressed that walking is more complex both for analysis and simulation than running due to the presence of the double support phase [200]. Sometimes this forces researchers to use separate algorithms for different walking phases when simulating the movement of the lower extremity: one for single support (an open kinematic chain) and the other for the double support phase (a closed-loop one) [217]. The leg depending on whether it is in contact with ground or not is said to be in stance and swing phases, respectively. Detailed description of the locomotion subcycles can be found in the paper by Nilsson et.al. [211]. Each extension/flexion step is characterized by its duration and associated lower and upper angle bound values. When the speed increases, the duration of the double support phase tends to zero that corresponds to transition to running.

One of the key features of walking is a firm contact of the support foot with the ground (unless, of course, the character is walking on banana peels). A method to ensure it using direct kinematics, as has been already mentioned, consists in changing the root limb of the skeleton when the support foot changes [54]. Bruderlin & Calvert have also applied similar approach to running simulation [55]. Control of foot position in inverse kinematics algorithms is achieved via corresponding constraint [42, 45].

Every human has its own recognizable style of walking. Still, to understand and simulate biped walking one has to search for general relationships.

Analysis of experimental gait data is a hard problem due to a number of reasons [62]:

- high dimensionality – data can include raw (measured) variables (such as kinematic, kinetic, electromyographic, metabolic, anthropometric) as well computed via inverse dynamics parameters^{xvii} (joint angles, velocities, moments etc.)
- temporal dependence – data gathered during walking at a self-selected pace have a quasi-periodic time dependence that hampers the use of classical methods for analysis of time series (assumption of stationarity is not valid)^{xviii}
- high variability – gait data exhibit intrasubject, intersubject and between-sample variabilities
- nonlinear relationships between the gait variables due to intrinsic nonlinear character of human movement dynamics

The recent review of the approaches to gait data analysis, both well known and relatively new, can be found in [62]. Multivariate statistical methods (principal component analysis, factor analysis, multiple correspondence analysis), fuzzy clustering, fractal dynamics, neural networks and discrete wavelet transform are considered. Among the most interesting results obtained, an attempt to clarify the relationships between the muscle activity and the lower-limb dynamics should be mentioned [254].

An extensive review of the mathematical problems related to locomotion control can be found in [261]. In particular, kinematics rules and synergetics of stepping movements in human and animals (from bipeds to myriapods) are considered and proposed that control of locomotion should be analyzed as a control of events in spacetime continuum. Another mathematical approach to the human gait based on the dynamics system theory is confirmed by recent observations [79] where gait transitions are interpreted as bifurcations between the attractors.

A fruitful approach to get insight into the internal mechanics of the human gait is a comparative study of walking in greatly different conditions and/or of different individuals.

Simulation of gait and gait initiation under reduced gravity has been reported in [49]. A variation of gravity can cause drastic change in the locomotion pattern, as was clearly demonstrated by astronauts "walking" on the Moon. The crucial role of gravity in human locomotion is not easily understood since it is

^{xvii}see, for example, [8]. It should be noted, however, that this problem as an inverse one is ill-posed and especially difficult to solve when the measured data are noisy. A least squares regularization to cope with problem of reconstruction of torques at joints etc. has been suggested in [155].

^{xviii}It explains, btw, that exact repetition of the walking cycle results in unnatural "sterile" motion, especially when viewed for an extended period of time.

present in the intersegmental forces relative to each movement and postural control. The author has considered a simple model of the double-inverted pendulum with one segment representing head-arms-trunk (HAT) and the other segment - the legs (LEGS). It has been assumed that the control torque between HAT and LEGS segments is proportional to the angular variation between segments with frequency dependent stiffness [51].

It has been shown that the natural body frequency (NBF) (which had been studied early by the same author with the aid of inverse dynamics methods [47]), being practically invariable for humans, is proportional to the square of the gravity. Moreover, this parameter accumulates kinetic effects of gravity and body characteristics in oscillating processes of gait and standing pose. The remarkable consequence is a universal dependence for humans of the gait initiation duration (the time needed to initiate and execute the first step) on NBF, whatever will be the characteristics of the steady gait. This is not true, however, for very young children: as was shown in an early paper [50] in contrast to adults, who adjust their gait initiation to match the target velocity, infants appear to use one general gait initiation "program" which takes more than one step.

Study of walking of children and adults revealed a parameter that is invariant with age: amplitude ratio of the centre of mass to the centre of pressure oscillations [48]. It should be noted that this amplitude ratio depends on NBF and thus will change in reduced gravity.

Understanding of invariant properties of the human walking is useful as a guiding principle for scaling of the captured or synthesized motion to different environment or character.

Another important aspect of biped walking is adaptation (adjustment) to the uneven ground. It was shown [190] that humans use an active knee-flexion strategy (with passive hip flexion) for avoidance of changes in terrain height while for accommodating they use an active hip-flexion strategy (with passive knee flexion).

A comparison of the gait characteristic of a modern woman and *Australopithecus afarensis* Lucy (AL 288-1) [136] has been made in [154]. The model used rigid segments to represent the foot, calf, thigh, and pelvis. Head, arms, and trunk (HAT) have been simulated as a lumped mass placed at the center of pelvis. The authors computed the energy that a hominid spent in moving her legs and trunk when walking. Energy is transferred between kinetic and potential components and between limbs. Since the system is neither perfectly balanced nor frictionless, some energy has been added and converted to the cost of locomotion. The needed segmental parameters (length, mass and mass moment of inertia) have been taken from [1] for a modern woman and estimated for Lucy. It was found, surprisingly, that Lucy spent less energy than the (composite) modern woman when locomoting at walking speeds. However, the preferred transition speed from walk to run (determined in accordance with [125] as such a speed that results in the maximum acceptable angular velocity of the ankle joint) is higher for the modern woman.

In [54] a human walking on flat ground has been animated using forward kinematics (procedural) approach. The basic locomotion style has been specified by three gait parameters (step length, step frequency, velocity).

Perhaps mainly due to ease of measurement, the speed-frequency relation, as determined from individuals walking over a treadmill, is the most widely used qualitative measure of the human walking, considered as a characteristic of the "natural" gait [211]. It was found that experimental data are fairly approximated by the power function with exponent value about 0.6.

However, recent experiments [32] have shown that the character of these relationships is drastically depends on the choice of the parameter that is held fixed during experiments (speed, step frequency or step length). The authors stressed that conventional theories (such as pendulum-based models or non-control "passive-dynamic" ones [191]) predict constant frequency independent on speed. They have succeeded in qualitative reconstruction of all three experimental curves numerically using constrained optimization. As the goal function, the metabolic cost of locomotion (oxygen consumption per unit distance) as a function of speed and frequency has been used.

One of the important by-products of their study is relative insensitivity of the optimal locomotion on the exact form of the goal function dependence on speed and frequency (assuming this function is convex and has a minimum for positive values of speed and frequency). They also suggested an explanation and a remedy for the optimization procedure that can remove a slight deviation from observations (minimum of the metabolic cost function is somewhat lower than a preferred walking speed): the only correction one needs to introduce is to penalize slowness, i.e. to add to the goal function a term that "rewards" speed.

One of the simplest dynamic model of human walking has been considered in [29]. It is a two link planar inverted pendulum which is made of a single rigid body and a supporting massless leg. The model behavior has been studied analytically and the knowledge obtained used for tuning a 15-segment body model.

Garsia [94] has performed an extensive study of simple passive-dynamics models introduced by McGeer [191] both in 2D (figures without and with knees) and 3D (with no knees). The main issues investigated have been gait efficiency and gait stability.

Nichols [209] has studied an approach to gait generation using periodic functions for specification of the foot's trajectory that results in a scalable gait with the step length, height and period as parameters. Proportional and proportional-integral controllers have been implemented for the control of biped walking robot.

An inverse dynamics study of human walking has been carried out in [87]. The authors included into the model contacts and friction forces. Constraints handling has been implemented via Lagrange multipliers. The simulated gait of a male was in good agreement with experimental data (the force exerted on the ground during the support phase has been compared).

A hierarchical motion control mechanism has been developed for interactive

animation of human walk in [69]. As the control hierarchy descends from the top, automation reduces while more control is given to the animator. A method computes foot placing automatically planning them two steps ahead of the current one. Bézier curves are used to represent trajectories of the swing foot and pelvis.

Sometimes the development of the controller for biped walking is based on some linearized model. Selection of control parameters and nominal trajectory determines the quality of control and in typical designs, some or all of the parameters are selected intuitively. The result is often not the best. If any special goal (such as to walk as fast as possible) is desirable, the design may become even harder. One possible alternative is to obtain the optimal or near-optimal design through parameter search. In [65] a genetic algorithm has been used to obtain the optimal design to achieve different goals, such as being able to walk on an inclined surface, walk at a high speed, or walk with a specified step size.

Prentice et.al. [232] have used a neural network model for generating electromyographic patterns observed in human walking. The network has two components. First, a recurrent network that receives tonic input is responsible for generating sine and cosine waveforms with the proper frequency. These waveforms are then shaped by a second feedforward network to give the actual electromyographic patterns for eight muscles of the lower limb and trunk. The results obtained using networks with different number of hidden units (4 and 16) are compared. A model has been used to produce a decomposition of central pattern generators into a self-sustaining oscillatory component and a shaping component. In a later paper [233] these authors consider artificial neural network models as an aid for representation of transformation of the kinematic plan into motor patterns. They have shown that a single trained network could generate muscle activation patterns for changes in the walking speed, the foot placement and the foot clearance.

Three supervised machine learning techniques for prediction of the activation patterns of muscles for walking assisted by a functional electrical stimulation (a multilayer perceptron with Levenberg-Marquardt modification of backpropagation learning algorithm; an adaptive-network-based fuzzy inference system; a combination of an entropy minimization type of inductive learning technique and a radial basis function type of artificial neural network) have been studied by Jonic et.al. [137]. The authors have shown that the last method provides the best generalization for the activation of the knee flexor muscles.

An approach based on the central pattern generators concept has been used to simulate human walking by Taga [265]. A model included 8 segments, 20 muscles and 7 pairs of neural oscillators. In the subsequent paper [266] the author has studied the obstacle avoidance that has been achieved by modulating the step length to provide a good foot placement and by adjusting the basic gait pattern so the swing leg would have a higher trajectory over the obstacle. The author has shown that (manually tuned) relatively small changes in the joint torques can lead to successful locomotion.

Running

Now, *here*, you see, it takes all the running *you* can do, to keep in the same place.
If you want to get somewhere else, you must run at least twice as fast as that!

Lewis Carroll

In [121, 123] controllers developed as state machines have been exploited to simulate running. State machines are used to enforce a correspondence between the phase of the behavior and the active control laws, limbs without required actions in a particular state are used to reduce disturbances to the system, inverse kinematics is used to compute the joint angles that would cause a foot or hand to reach a desired location. Six states have been considered: flight, heel contact, heel and toe contact, toe contact, loading and unloading. The last two states of very short duration are needed to ensure the support (active) leg position before invoking corresponding control actions.

The points of contact between the feet and the ground have been modelled via constraints. It should be noted that such simple description of the contact may be insufficient for producing realistic running over terrain with variable properties. The authors of [88] assume that the leg and running surface can be modelled as two linear springs in series. They use simulation results as well as human data to show that runners quickly adapt their effective leg stiffness to suit the terrain stiffness during steady state running.

The rigid-body models of the man and woman are realistic because their mass and inertia properties are obtained using algorithms for computing mass and moment of inertia of polygonal object of uniform density [174] and density data measured from cadavers [77]. Each internal joint has a very simple muscle model, a torque source. The runner has 17 body segments and 30 controlled DOFs.

To simplify the problem of specifying the control laws, several limbs are often used in a synergistic fashion. For example, the ankle and knee joints of the simulated runner work together to push off the ground during the stance phase. Wherever possible, the control laws use the passive behaviors of the system to achieve a desired effect. During the stance phase, the runner's knee acts as a spring, both compressing to store the energy and then extending to release that energy. For the simulation of running, the control laws make the athlete's arms swing in opposition to the legs.

A running model based on a one-legged planar hopper with a self-balancing mechanism has been proposed in [139]. A controller for human running has been based on the energy consumption.

Influence of inertia on intersegment moments of the lower extremity joints during running have been studied by Krabbe et. al. [153]. The authors have shown that this effect could be neglected for the ankle but is important for the hip.

2.5.2 Aerial Movements

Yet you turned a back-sommersault in at the door -
Pray, what is the reason of that?

Lewis Carroll

Gymnasts, divers and free style skiers perform extremely complex aerial maneuvers. An airborne athlete can not apply any external forces or torques to the body so the trajectory of the center of mass is determined and angular momentum is fixed from the moment of takeoff to the moment of landing, neglecting aerodynamic forces. However, there are well known aerial movements that at first sight violate conservation of angular momentum such as: 1) divers leaving the board with rotation about a side-to-side (sommersault) body axis only, can subsequently produce rotation about their head-to-toe (twist) body axis [90] and 2) a cat falling with no net angular momentum can straighten itself in flight to land on all four paws [138].

It turns out that an athlete can actively influence aerial motion by the relative movement of the limbs and torso during the flight. There are three techniques that provide such control over the motion [225]:

- change of the moment of inertia about an axis by means of grouping the body in order to change the rotation rate about that axis
- reorientation maintaining zero angular momentum by performing a sequence of the limb movements
- reconfiguration of the body in such a way that the principle axes of inertia are reoriented relative to the inertially fixed angular momentum vector

The stability of aerial motion is of primary importance since even small errors accumulated during a relatively long flight could result in a disastrous landing. There are two possible control mechanisms that can generate compensative movements. The first one is an active one that assumes that athlete senses disturbances and generates ("computes") appropriate responses. Playter [225] argues that complexity of this feedback control approach would force high demands on the athlete's perceptive and motor control abilities. As an alternative an open loop passive dynamics control is suggested. Control efforts (torques at joints) during an aerial maneuver are just replayed from memory and compensatory movements are "computed" by the physical system as part of its natural behavior

The author has shown that a few gymnastic movements (the tucked front somersault, the back layout somersault and the front somersault with one and half twist) could be simulated with passive stabilization that results from the natural dynamic interaction of the limbs and the body during the flight. Stabilization arises from the inherent tendency of the arms to tilt in response to the twisting motion of the body. The arm tilt forces the principle axes of the system to move in a direction that compensates for tilt and twist errors. The author

proved the possibility of passive stabilization using a simple model: the head, torso and legs are considered as a single rigid body while arms could be raised and lowered. Torques at the shoulder joints are provided by torsional springs and dampers. The model (neglecting translation of the centre of mass) had five degrees of freedom: three for the rotation of the body and two for the relative motion of each arm [225]. This simple three-body model exhibits stable somersaults if spring used at the shoulder is adjusted correspondingly. It should be noted that Yeadon & Mikulcik [306] do not accept the generality of the Playter's conclusions. They agree that passive stabilization can be effective when the arms are abducted more than 30° from the midline of the body. It is, however, insufficient when somersaults are performed with the arms adducted close to the body and then stability could be achieved using proportional-derivative controllers. The authors have studied different strategies for controlling twist in twisting and nontwisting somersaults using a 11-segment model: 1) symmetrical arm abduction; 2) arching of the body; 3) asymmetrical arm adduction/abduction.

A simulation of the female gymnast performing a vault from the spring board over the vaulting horse has been reported in [123]. The model has 15 segments and 30 DOFs. State machine was used to control the motion with the following states: hurdle step, board contact, first flight, horse contact, second flight, landing.

A rather sad example of the human aerial movement is reported in [114]. The author, being called as an expert to the court, simulated an overrotated rock'n roll Betterini somersault that ended by the severe injuries of the female dancer when she hit the floor with her chin.

A simulation of a human diver with 38 controlled degrees of freedom has been described in [300]. The human model can perform a number of 10 meter platform dives. The dynamic model of the diver consists of 15 rigid bodies connected by the rotary joints. The dynamic properties of the rigid bodies were calculated as for the runner model described in the previous section.

The control system for the diver is hierarchical. The low-level control is provided by proportional-derivative servos that move the joints towards their desired positions. Balance on the diving board is provided by a controller at the ankle that computes the angle for the ankle that would place the body's center of mass over the feet. This angle serves as a desired angle for the low-level PD control. High-level control for the dive is provided by a state machine that alters the desired configuration of the diver. Five states are used in the 10m platform dives: Compression, Decompression, Flight-Phase 1, Flight-Phase 2, and Entry. The high-level control alters not only the desired values for the joints but also the gain on the low level PD servos. For example, the gains required for the compression phase of the dive are higher than the gains required for the flight phase. The gains and set points for the controllers were tuned by hand to ensure that the diver performs the dive and enters the water vertically. Still the model of muscles used by Wooten and Hodgins was very simple (a torque source at each joint) and the strength of the individual joints was not taken into

account. This simplification, as the authors themselves noted, could results in a simulated human that is stronger or faster than a real one and can perform motions impossible for humans.

2.5.3 Arm Movements

neither shall ye touch it
Genesis, 3, 3

A great variety of human arm movements can be classified into a number of groups such as

- Goal-directed manipulation:
 - changing position: lift, move, raise, push, pull, draw, jerk, toss, throw, hurl, thrust, shake etc.
 - changing orientation: turn, spin, rotate, twist
 - changing shape: fold, stretch, bend, spread, squeeze etc.
 - contact with object: grasp, seize, grab, embrace, grip etc.
 - joining objects: tie, nail, sew, bind, pin, envelop etc.
- Empty-hand gestures: wave, snap, point, show, shrug etc.
- Haptic exploration: touch, stroke, knock, throb, tickle, hit, slam, tap, kick, pat etc.

karla et.al. [140] cite another taxonomy:

- **Semiotic:** to communicate information
- **Ergotic:** to manipulate and create objects
- **Epistemic:** to explore environment

In this section gross arm motion is considered. The discussion of the animation of fine hand movements such as grasping, for example, can be found in [38, 197].

Reaching motion is obviously one of the most frequent arm movements. This motion has been studied extensively due to both the relatively simple experimental setting and its importance for ergonomics.

The general features of the reaching motion are well known [61]:

- the trajectory, if unobstructed, is nearly straight.
- the velocity profile is bell shaped.
- the acceleration profile has two peaks.

- any mass added to arm tends to reduce the velocity and acceleration values

It is also well known (starting from N. Bernstein observations in 1920s) that the straight trajectory of the end-effector does not prevent the trajectories of the intermediate joints to be very complex^{xix}.

Numerous experimental studies of hand periodic ("rhythmic") motions revealed the power law (referred to as "2/3 Power Law") relationship between the tangential velocity and the radius of curvature of the end-effector trajectory^{xx}. It has been considered as a fundamental invariant of the central nervous system in the formation of rhythmic endpoints trajectories and even as an assessment criterion for the quality of motion models [249]. However, Schaal & Sternad in the just cited paper published this year have shown that this law is valid only for planar trajectories of relatively small size almost exclusively studied in the precedings works. Analysis of the 3D endpoint trajectories demonstrates that deviations increases with the pattern size.

The authors explanation of this disagreement is based on the hypothesis that a power law is a by-product of the smoothness of the endpoint trajectory. A similar opinion is supported by Todorov & Jordan [273] who used in their studies "minimum jerk" optimization criterion (which is equivalent to minimization of the higher frequency components of the trajectory). The crucial step in Schaal & Sternad analysis is to assume that smoothness is implemented in the intrinsic joint space coordinates. For small patterns it results in smoothness in Cartesian coordinates due to linear transformation between the joint coordinates and endpoints coordinates. The behavior for large patterns is explained by the non-linearities of these transformation. The authors righteously argue that these results indicate the primary role of the joint space in motion generation. They, however, warn that smoothness in joint space (and, hence, minimum jerk movements and minimum torque changes) is a criterion valid for rhythmic movements that could fail for discrete movements^{xxi}.

In another paper [264] these authors have analysed two hypothesis of movement segmentation of endpoints trajectories in human drawing movements. The kinematic characteristics of the endpoint trajectories and the seven joint angles of the arm have been studied. The authors have concluded that while the endpoints exhibit segmentation, the joint angles show continuous oscillatory patterns. This phenomena is explained by the nonlinear transformations of the forward kinematics of the arm. The authors suggest that the rhythmic drawing movements are described best in terms of continuous oscillatory pattern generators in joint space.

It is worth to note that joint space coordinates are thought to be the coordinates use to encode reaching movement direction ("spatial preferred direction")

^{xix}The problem of understanding how human body overcomes an excessive number of degrees is called sometimes "Bernstein's problem" [61]

^{xx}In fact 2/3 power law is formulated for the angular velocity a proportional to the curvature c of the end-effector path $a \sim c^{2/3}$. The dependence of the tangential velocity on the radius of curvature is written as $v \sim r^{1/3}$.

^{xxi}since rhythmic motion is phylogenetically older than discrete one, they could use different neural circuits [249].

in the primary motor cortex of primates [5]. The authors of the cited paper considered three coordinate systems (in addition to the joint coordinates, Cartesian and shoulder-centered) 2-DOFs planar arm. The joint coordinates best explain observed cellular response patterns data for the curved motion experiments.

The framework of the equilibrium point hypothesis has been used by Latash et.al. [163] to reconstruct equilibrium trajectories of the elbow and the wrist during fast voluntary movements. An explicit relation between control variables to the two joints has been suggested as the implementation of the simple synergy. Sainburg et.al [246] have studied reaching movements and have found that a three-stage system sequentially links anticipatory, error correction and posture mechanisms to control intersegmental mechanics.

A model for simulation of reaching movements that contains 2-DOFs planar manipulator, a Hill type model of 6 muscles and artificial neural net to represent the nervous system has been developed by Karniel & Inbar [141]. The results obtained are considered by the authors that the central nervous system able to generate typical reaching movements with a simple feedforward controller that controls only the timing and amplitude of rectangular excitation impulses to muscles. It has been also shown that nonlinearity of the muscle properties is essential for achievement of such type of control.

Over-arm throws constrained to the sagittal plane have been studied in [68] using a muscle-actuated two-segment model representing the forearm and hand. The moments at the joints were produced by the muscle-tendon models representing the net action of the elbow extensors and wrist flexors. The controller had to specify the times of the activation of each muscle-tendon and the time of release of the ball. The study had shown that the timing accuracy of the muscle action should be rather high. The task was completed in less than 150 ms which is too fast for afferent signal feedback to be received, processed, appropriate efferent signals sent to the muscles and a change in the force occurs. Thus, as the authors argue, such muscle action must be pre-planned.

A simple model of a two-segmented arm with only two muscles have been used in [75] to study an underarm throw and overarm stroke. They authors have found that, due to series tendon compliance, there are often two distinct optimal delays for a muscle with given moment arms. The choice of a global optimum out of two depends on the strength of other muscles and the weight of a load, usually a shorter delay being advantageous for heavier load.

Different cyclical elbow-wrist movements, including unidirectional rotations at the elbow and wrist in the same direction, bidirectional and free wrist motion, have been studied in [81]. The authors have shown that control at the elbow was principally different from control at the wrist. Elbow control in all three movements studied was similar to usually observed during the single-joint movements and largely independent of wrist motion. The elbow muscles were found to be responsible not only for the elbow motion, but also for generation of torques that play an important role in wrist control. These torques are their primary source of wrist motion. The authors have proposed a hierarchical organization of the elbow-wrist coordination: the elbow muscles generate movement of the whole linkage while the wrist muscles provide a fine correction of the

motion.

The patterns of joint kinematics and torques of planar arm reaching movement in the sagittal plane have been considered in [101]. Dynamic muscle torques have been calculated via inverse dynamics method neglecting gravity. The dynamics components of the muscle torques at the elbow and the shoulder have been almost linearly related to each other for the movements in almost all directions. Both have been similarly shaped symmetrical pulses. This effect is called by the authors *linear synergy*. The relative scaling of the torques at two joints has been found to depend on the movement direction. The authors argue that their results, not being incompatible with other hypotheses of motion coordination, are best explained assuming that voluntary, multiple degrees of freedom rapid reaching movements may use rule-based, feedforward control of dynamic joint torque. This control system may operate in parallel with a positional control system that maintain body balance.

A detailed model of the elbow, forearm and wrist has been developed in [169]. The model contains the humerus, radius, ulna and hand connected by the appropriate joints. Twenty muscles have been included into the model. They were simulated by a force producing contractile element in a series with a tendon that has been modelled as a spring of constant stiffness. The unusual feature of the model is the account for the limit joints angles via passive moments added at the joints. These moments have been determined using experimental information. One of the conclusions of the authors is the high sensitivity of the model to the muscle length and tendon slack length.

The biologically motivated approach to the automatic generation of the life-like gestures is proposed by Kopp & Wachsmuth [152]. The authors have combined knowledge-based techniques with a trajectory generation method based on parametric curve composition using splines. The articulated figure used in the cited paper contained 43 DOFs for the main body and 20 DOFs for each hand.

Kinematics of reaching has been studied by Hestens [119] using developed by him geometric algebra approach (see the section **Kinematics approaches**). The author follows Bullock and Grossberg [57] assuming that, since the experimentally observed hand trajectory is straight, hand position end points are *control variables* for reaching movements. A general formulation of the kinematics of reaching is presented and solution of the inverse kinematics problem that parametrizes the joint angles in terms of the wrist position is derived. An advantage of the proposed formulation of the basic *reaching equation* is its coordinate-free form. As the control variables *the target direction* and *the arm extension* are used.

The author also considers general questions of quantitative description of the neural sensory-motor system. Since body kinematics is the geometry of movement, the accurate motor control could be achieved if this geometry is reflected somehow at all the levels of sensory-motor processing. He advocates the use of the term "neurogeometry" [222] to describe the mathematical theory of motor control.

Schouten et.al. [253] have studied the effect of the frequency on the reflexive

feedback gain of human arm using a 2-DOFs model with six muscles. A two-step procedure has been used: 1) optimization of static muscle activations; 2) optimization of reflex gains using an "additional control effort" criterion. The results show that for a given posture shoulder muscles have the largest contribution while the biarticular muscles have a relatively small contribution to the behavior. The modest deviations from the experimental data are explained by the unmodelled mechanical effects of the cross-bridges in the Hill-type muscle models.

Chi et.al. [66] have animated arm movement using EMOTE (Expressive MOTion Engine) system developed by the authors recently. The system defines motion in terms of Laban motion analysis notation in which, for example, "Effort" has four attributes (Space, Weight, Time, Flow) while "Shape" has Horizontal, Vertical and Sagittal "dimensions". The arm model has 1-DOF elbow joint and spherical 3-DOFs shoulder and wrist joints.

2.5.4 Miscellaneous Movements

Various planar gymnastic exercises (transversing a set of irregularly-spaced monkeybars, climbing a ladder, fall recovery have been simulated in [162] using motion primitives and state machine control. The character of these primitives for, for example, monkeybars is as follows: "grasp closest rung", "grasp rung following closest rung", "pull up using support arm" etc. As the authors state, this approach is still far from reproducing complex 3D human motions.

The difficulty of simulations of such motions as flips and jumps arises from the need for an accurate timing for a successful execution. In [130] a decision-tree search algorithm has been used to model such motions in 2D.

The model of the leg consisting of three rigid bodies activated by nine muscle groups has been exploited in [277, 276] to study a vertical one-legged jump. Three phases have been analyzed starting from the squat position till the stabilization of the body after landing.

Quasi-elastic behavior of joints in such movements as jumping have been investigated in [255] using an elastic three-segment leg model. The effective operation of the muscles crossing the knee and ankle joints has been described in terms of rotational springs. The authors have found, in particularity, that a three-segment leg tends to become unstable at a certain amount of bending expressed by a counter-rotation of the joints; nonlinear joint torque-displacement behavior extends the range of the stable leg bending; biarticular structures (such as a human gastrocnemius muscle) and geometric constraints support homogeneous bending in both joints. The future study should account for the segments masses and moments of inertia and dissipative joint operation (such as a heel pad deformation).

A movement strategy of the human forward trunk bending has been studied in [7]. The authors note that two functionally different behaviour goals are achieved during this movement: the bending itself and the maintenance of the equilibrium. They try to decompose the motion into three dynamically independent components connected with the hip, knee and ankle movements.

The results show that the hip and the ankle movements can be treated as the independently controlled motion units and it is proposed that central nervous system controls this motion sequentially to perform the bending and to maintain equilibrium.

A planar model for lifting activity has been used in [17] to check a hypothesis that the body tries to minimize the work to be done. The goal function has been also subjected to a number of constraints that include the physical workplace and maintenance of balance. The results computed for the body model containing 5 rigid links were in good agreement with experimental data.

A simulation of the finger motion in the sagittal plane assuming minimum of the expenditure of energy is done in [258]. It is difficult to understand what model of a tendon was really used: the authors refer to the tendon as "an inextensible filament" in the model description, but later speak about "changing of tendon length".

Hestens has studied the oculomotor system for accurate gaze control and in particularity *saccade* [119]. Saccade is a rapid shift of gaze in order to fixate a target object in the visual field. For kinematic purposes, the eye is simulated as a ball in a socket joint, so it has three degrees of freedom. There exists a number of experimentally proven laws of neurobiology. One of them (Listing's law) asserts that there is a unique gaze direction, called the *primary direction*, such that any saccade is obtained from it by parallel transport along the geodesic. The main body of the paper is devoted to investigating implications of Listing's law. The main problem is to understand what control parameter central nervous system uses to control pursuit of the moving object with gaze. In the considered paper the optokinetic model of the human gaze is developed and analyzed.

Ballroom dancing studied by Lake & Green [156] gives an example of a motion which decomposition into primitive movements is relatively simple and can be done hierarchically. Each dance can be divided into a set of motion sequences called *patterns*, with a typical duration of 2 to 10 seconds. Each pattern, in turn, consists of a sequence of *positions* that define location and orientation of the body after a specified time interval (step). Almost all patterns are composed of the transitions between the five fundamental positions [156]. Motion control used by the authors is based on a finite state machine approach. A limb may be in one of three motion states:

1. "Free swing": all internal torques are set to zero.
2. "Move": torques should provide smooth transition of the limb from the starting to the final position within the specified time limit.
3. "Maintain": as the name suggests the limb should be kept in a fixed angular position relative to its parent, thus large restorative torques are applied in case of deviation from the current position.

The task manager calculates the time needed to complete the step and initiate timers for all links whose state should be set to "Move". Rotational matrices describing the current position are converted to the quaternions since interpolation along the quaternions curves is preferable. The authors encountered a

problem in the implementation of their method for articulating relatively simple figure that manifests itself as limb oscillations leading to numerical instabilities. The remedy used in the paper is hardly a good one: moments of inertia for each link were multiplied by a factor of 300 (!).

Multilegged Locomotion

A large amount of nonsense has been said about this subject, not only by ordinary people but even by excellent scientists and anatomists, who prefer to pass on incorrect second-hand theories, rather than trust their own observations.

Giovanni Alfonso Borelli, De Motu Animalium (1680)

Multilegged locomotion is not directly related to the human motion (except in cases when a human uses all her/his extremities to achieve a greater stability of gait). Still, the studies of this topic are of considerable interest due to the differences of problems of, first of all, motion controllers development and other characteristics, and enlarge our knowledge in biped locomotion as well.

Different approaches to neuromechanics of legged locomotion have been analyzed by Full & Koditschek [91]. The authors have listed 12 hypotheses of the organization of legged locomotor systems. They suggest the hierarchy organism \Rightarrow anchors \Rightarrow templates. "Templates" are the simplest models that exhibit a desired behavior and disregard skeletal type, leg number etc. Examples of templates are a well-known model of spring-loaded inverted pendulum that describes motion in the sagittal plane and proposed by the authors lateral leg spring model that simulate animals bouncing from side to side. "Anchors" are elaborate models grounded on the morphological and physiological data that should account for the multiple legs, joint torques that actuate them, the recruitment of muscles and control by the nervous system. The creation of the templates is aimed at the resolution of the redundancies of multiple legs, muscles and joints by exploiting synergies and symmetries.

Surprisingly templates turned out to be rather universal for the terrestrial locomotion. Moreover, such a parameter as a relative leg stiffness in the spring-loaded inverted pendulum model is similar in six-legged trotters (cockroaches), four-legs trotters (dogs), two-legged runners (humans) and two-legged hoppers (kangaroos) [91].

Walking of quadrupeds is similar to that of humans and can be considered as two bipeds walking in front of the other, moving their limbs with a phase shift of 3/4 of the cycle [194]. Similarly, a trotting quadrupeds can be presented as two running bipeds with a phase shift of a half of the cycle (or zero for gait of quadrupeds called the rack). Quadrupeds also exhibit a few variants of high-speed gait – gallop – that is analogous to human skipping (the latter is not a favorite humans locomotion gait since it is 50expensive energetically than running at a comparable speed [194]).

Statistically stable multi-legged motion has been studied in [192]. It has been shown that when more than two legs are always support the articulated character, the center of mass is generally lies in the sustentation polygon. In this case in contrast to the human walking the balance control is a less important issue than the coordination of the legs.

In [73] a model of six-legged walking is described optimized by reinforcement learning to achieve stable motion. The cost function is based on the frequency of the model's loss of stability evaluated for randomly chosen initial leg positions. Genetic algorithm has been used at initial stages of optimization to get to the vicinity of the global minimum followed by a Monte Carlo method to search a smaller space of solutions.

It should be noted that the six-legged locomotion is unique in that sense that absolutely stable motion is possible (at least theoretically, assuming ideal coordination) when alternatively three legs are in the support phase. If alternating tripod gait (first and third left legs move in phase with second right one all three in anti-phase to the opposite tripod) a tripod acts as a single virtual leg and coordination of the motion is similar to that of bipeds [92]. Six-legged insects tend to have the shortest swing period possible and as speed increases the swing period changes little and the stance period decreases [146].

Mullerwilm [199] has simulated the coordinated interaction between the walking legs of a multi-legged animal using a neural network consisting of the separate modules with oscillatory capabilities. A variant of reinforcement comparison learning has been used to train the network.

Trajectory-based optimization of the quadruped locomotion has been reported in [275]. To simplify the problem the authors restricted themselves to optimization of the motion trajectories of two key mass points instead of all degrees of freedom. Another remarkable feature of their work is, as they formulate, "the capability to stretch the laws of physics if necessary": both physics and "comfort" are treated as constraints that can be satisfied only approximately.

The simplified model consisted of two point masses connected by a spring that served to model the internal forces of the back of the quadruped. The trajectories have been represented as C^2 piecewise-continuous splines.

Animation of the motion as well as animation of the growth of animals has been studied in [289].

Ito et.al. [133] have developed a central pattern generator model that can account for periodic perturbations from the environment and adaptation of quadruped locomotion. The model accounts for three types of dynamics: environmental, rhythmic motion, and adaptation dynamics. Authors argue that the time scale of adaptation dynamics should be much larger than that of rhythmic motion dynamics.

Klavins et.al. [146] studied two schemes for coordination of multilegged locomotion (central pattern generator and reflex driven coordination) using two simple models:

1. "bipedal bead on a rail" (BBR)
2. "bipedal spring loaded inverted pendulum" (BSLIP)

One of the aims the authors declare is to develop an "interpolation" between the pure feedforward and pure feedback coordination mechanisms.

2.5.5 Large-scale Numerical Simulation of Human Motion

And what is the good of a small dare, Roger?

William Golding

Detailed models of muskulotendon system allow researches to perform very accurate computations of human motion. Unfortunately, these models are extremely computer intensive.

A number high-performance computations of human motion were carried out by Anderson & Pandy and their colleagues. The model complexity so far ranges from 14-DOF actuated by 46 muskulotendon units [11] to 10-segment, 23-DOF skeleton actuated by 54 muskulotendon units [10]. The head, arms and torso (HAT) in the last model were lumped into a single rigid body, and this segment articulated with the pelvis via a 3-DOF ball-and-socket joint. Each hip was modelled as a ball-and-socket joint while a knee as a 1-DOF hinge. Two segments were used to model each foot.

Each leg was actuated by 24 muscles, and the movements of pelvis and HAT were provided by 6 abdominal and back muscles. Each actuator in the model was represented by a three-element Hill type muscle in series with elastic tendon^{xxii}. Parameters describing the mechanical properties of each muscle were obtained from the literature and scaled to the strength of individual subjects. The interaction of the feet with the ground was simulated using a set of spring-damper units distributed under the sole of each foot.

To solve the optimization problem the authors of [10] discretized the excitation history of each muscle into a set of 15 control nodes which became independent variables. A minimum of metabolic cost per unit distance had been chosen as a goal function.

It is useful to cite some figures that show the scale of computations. A 14-DOF model required about 3 months of dedicated processing time on SGI Iris 4D25 or 77 and 88 hours on Intel iPSC/860 and Cray Y-MP 8/864, respectively [11].

The authors have analyzed performance of different computers using a conventional serial machine, a parallel-vector-processing machine, and a multiple-instruction/multiple-data (MIMD) parallel machine. The serial optimal control algorithm decomposes very efficiently into a parallel algorithm. It consists of three parts: (1) forward simulation, (2) computation of derivatives, and (3) parameter optimization [9]. Of these three parts, computation of the derivatives dominates total CPU time (i.e., over 90 percent). When implemented on a MIMD supercomputer, computation of the derivatives scales almost linearly

^{xxii}It has been shown in [114] that Hill-type models are oversimplified and sometimes produce grossly erroneous results.

with the number of processors used. Specifically, on any MIMD computer, the authors were able to compute derivatives 100 times faster with 128 processors than with just 1 processor. In contrast, the Cray performed best during parameter optimization of the controls, executing the parameter optimization routine 37 times faster than the serial machine. The ideal computer architecture for solving very-large-scale optimal control problems appears to be a hybrid system in which a vector-processing machine is integrated into the communication network of a MIMD parallel machine [294]. Later computations have been performed on an IBM SP/2 at the NASA Ames Research Center and Thinking Machines Corp. CM-5 computer, and have consumed thousands hours of CPU time [292]. One of the main achievements of this study is a possibility to simulate different motions (in this case high jumping and gait) using the same model. The authors argue that development of high performance computers will make too expensive the development of simple models for a specific motion and universal models will dominate in the future [10].

A detailed neuromuskular model has been used by Ogihara & Yamazaki [213] to simulate human gait. It consisted of 7 rigid links in the saggital plane with 9 muscles and a sensory-motor nervous system. The complete model includes 76 differential equations. Genetics algorithms have been used to tune 93 parameters exploiting energy expenditure per unit distance travelled as a goal function. The generated walking patterns were in good agreement with the observed ones.

DR. RUPNATHJIK (DR. RUPNATHJIK)

Chapter 3

Conclusions

This is not the end, it is not even the beginning of the end. But it is, perhaps, the end of beginning.
Winston Churchill

The present brief review of the physically based animations of human motion shows that methods are mature enough to produce high quality results for a large class of motions. However, there are a few problems that require additional study.

3.1 Known Problems

Complex problems have simple, easy-to-understand wrong answers.
Murphy's Law Book Two

The following list is probably incomplete and the order of issues is rather arbitrary.

- *Soft tissue segmentation.* The development of an articulated model encounters a problem when one has to define different soft tissue segments and to describe sharp intersegmental boundaries. This task is relatively easy for the head and the extremities. However, it is difficult to cut for segments the neck, abdomen or thorax: these body parts are hardly can be called soft tissue segments since they consist of a complex bone structure connected to various types of soft tissue¹.
- *Non-rigidity of the body segments.* Part of the body segments (muscle, connective tissues etc.) can execute movements relative to the skeleton.

¹For example, a reasonable division of the thorax into segments is practically impossible (one has a choice: to consider the abdomino-thoracic complex as a single rigid body or try to create a realistic thorax model that would include over three hundreds hard- and soft-tissue subsegments).

Moreover, the properties of the relaxed and contracted muscles are quite different. In [114] a thesis by Gruber(1987) is cited. The author studied reaction forces and moments in the knee and the hip during vertical-jump landing using two three-link models: a rigid one and a model where "wobbling" masses had been attached to the rigid links. She found that difference between the models could be up to a few thousand (!) percent. Hatze [114] noted that these two models are the extreme ones and in reality the muscle properties vary continuously.

- *Muscle models.* Majority of the dynamics-based simulations use a simple muscle model, in best case a three-element Hill's model. As has been already noted, more accurate models are needed to provide adequate results.
- *An issue of choice of a goal function for optimization problems.* As it was shown in [32], a minimum metabolic cost of locomotion, i.e. oxygen consumption per unit distance is a reasonable choice that provides good results for a number of motions. However, the authors themselves admit that agreement with experimental data can be accidental and in reality quite different cost functions are used by humans (for example, energy per unit time). They also state that another cost function could be required for different kind of motion (such as carrying loads, walking bent over under overhead obstacles or walking with the aim to make no noise while hunting, for example). In [67] it has been shown that humans appear to minimize energy expenditure when walking on level ground but not when stepping over obstacles: they use the larger-than-necessary obstacle clearance.
- *Obstacle avoidance.* To the author's knowledge, up to date there is no sufficiently general and fast method that will behave robustly, for example, for two highly articulated figures' encounter in some kind of fight.
- *Computational cost.* The detailed models of human motion require huge computational resources. Use of neural nets for emulation of real physical processes [76, 109] is quite promising. Still, systematic research to asses the spinnal network architecture and learning algorithms is needed. A special attention should be paid to hierarchical networks as the most perspective ones for control of hierarchical articulated figures.
- *Transient motions.* That seems to be one of the most difficult issues where the motion capture could not be of great help. If you have the motion of a running human and that of a lying, hardly even intelligent procedures such as the neural nets trained on these examples will provide realistic generalization for falling: evidently, in this transition some body parameters (masses and moments of inertia) will play a crucial role while they are relatively unimportant in both running and lying and thus cannot be learned by the neural nets.

3.2 Physically-Based Simulation Engine for Animation

Wisdom consists of knowing when to avoid perfection.
More Murphy's Law

The features an ideal animation system should provide are evident:

- character's adherence to anatomy
- character's adherence to physiology
- physically accurate motion (if an animator does not specify a controllable exaggeration)
- personification of the character
- character's ability to master motor skills
- character's interaction with environment and other characters
- efficiency
- compatibility of the data structure to that of rendering software

This is certainly a toll order. Three less ambiguous problems for which physically-based simulation seems to be important are the following ones:

1. Blending of captured motions
2. Retargetting of captured motion
3. Continuation of captured motion

It is worth to note that while the use of the underlying biology and physics is *desirable* for the first two problemsⁱⁱ, it is *mandatory* for the third one if the character of motion is to be changed as a result, for example, collision ("unintended" motion). Retargetting can be considered in very broad sence: it can be an adjustment to a new character, to a new emotional state of the old one or to environment.

Implementation Tools

The absence of alternatives clears the mind marvelously.
Henry Kissenger

ⁱⁱit has been already stresses, however, that blending of cardinally different motions by pure geometrical or signal processing methods can give very poor results

To develop an efficient physically-based simulation core for animation system one should use (wherever possible) and modify (wherever necessary) existing techniques. There are a few guidance principles that should be respected:

- hierarchical approach for
 - skeleton & muscle representation
 - constraints
 - kinematics & dynamics
 - control
- adaptivity (variable resolution) via use of
 - "passive" DOFs
 - reconstruction of missing DOFs
 - natural dynamics
- knowledge-based high-level motion control (domain-specific rules & control parameters)

Probably the most important tools for achieving the aims formulated are multiresolution analysis (either B-spline or wavelet) and artificial neural netsⁱⁱⁱ. The former provides the decomposition of the motion into the basic one and "style" (personality) and thus creates the basis for the motion transformations.

Neural nets could be used either as universal approximators (for example, as efficient muscle & dynamics models) or in data mining mode to extract hidden relationships among motion parameters.

The most important application is probably for motion controllers generation: an animator has no choice when dealing with unintended motion and has to use forward dynamics based methods. One should distinguish different kinds of motion depending on the role of motor control system: kinematic tasks (slow motions in which dynamics effects are not significant), reflex-like behavior ("pre-computed" motions that can be modified on fly while maintaining some invariant characteristics) and dynamic servoing (the laws of mechanics are to be integrated in this case). A notion of primitive movements ("eigen-movements") that can be expressed as stereotypical trajectories should be examined in two aspects: extraction of these entities from captured or generated motions and their superposition/sequencing as means to generate new motions (and first of all to provide reflex-like behavior).

A less formal conclusions can be found in Appendix.

ⁱⁱⁱNeural nets used for data analysis (with a few exceptions such as counterpropagation and self-organizing maps) are equivalent to the well known statistical methods being usually much more slow. For example, the most popular neural networks called multilayer perceptrons are just nonlinear regression and discriminant models. Standard learning algorithms are inefficient because they have been designed for massively parallel computers. On a serial computer neural nets can be trained more efficiently by standard optimization algorithms.

Bibliography

- [1] *Anthropometric Source Book*. NASA Publication No. 1024, Houston, 1978.
- [2] J. K. Aggarwal and Q. Cai. Human motion analysis: A review. *Comput. Vis. Image Und.*, 73(3):428–440, 1999.
- [3] J. K. Aggarwal, L.S. Davis, and W.N. Martin. Correspondence processes in dynamic scene analysis. *Proc. of the IEEE*, 69(5):562–572, 1981.
- [4] M. Aigner and J. Heegard. One-dimensional quasi-static continuum model of muscle contraction as a distributed control system. *Center for Turbulence Research, Ann. Res. Briefs*, pages 155–168, 1999.
- [5] R. Ajemian, D. Bullock, and S. Grossberg. Kinematic coordinates in which motor cortical cells encode movement direction. *J. Neurophysiol.*, 84:2191–2203, 2000.
- [6] M. Alexa, D. Cohen-Or, and D. Levin. As-rigid-as-possible shape interpolation. In *Proc. of SIGGRAPH 2000*, pages 157–164, 2000.
- [7] A.V. Alexandrov, A.A. Frolov, and J. Massion. Biomechanical analysis of movement strategies in human forward trunk bending. II. Experimental study. *Biol. Cybern.*, 84:435–443, 2001.
- [8] T. Alkjaer, E.B. Simonsen, and P. Dyhre-Poulsen. Comparison of inverse dynamics calculated by two- and three-dimensional models during walking. *Gait Posture*, 13:73–77, 2001.
- [9] F.C. Anderson and M.G. Pandy. Musculoskeletal models and computational algorithms for the numerical simulation of human motion on earth and in space. <http://sdca.gfc.nasa.gov/ESS/annual.reports/ess95contents/app.gci.pandy.html>.
- [10] F.C. Anderson and M.G. Pandy. Dynamic simulation of human motion in three dimensions. In *Proc. of the 6th Int. Symp. on the 3D Analysis of Human Movement*, pages 1–4, Cape Town, South Africa, 2000.
- [11] F.C. Anderson, J.M. Ziegler, M.G. Pandy, and R.T. Whalen. Application of high-performance computing to numerical simulation of human movement. *J. Biomech. Eng.*, 117:155–157, 1995.
- [12] K.I. Anjyo, Y. Usami, and T. Kurihara. A simple method for extracting the natural beauty of hair. In *SIGGRAPH'92 Proc.*, pages 111–120, 1992.
- [13] G.D. Ariel, R.J.C. Buijs, and S.G. Chung. Visualizing orientation using quaternions. In *Proc. of the 6th Int. Symp. on the 3D Analysis of Human Movement*, pages 25–28, Cape Town, South Africa, 2000.

- [14] W. Armstrong, M. Green, and R. Lake. Near real-time control of human figure models. *IEEE Comput. Graph.*, 7, 1987.
- [15] V. Arnold. *Mathematical Methods of Classical Mechanics*. Springer, 1989.
- [16] J. Auslander, A. Fukunaga, H. Partovi, J. Christensen, L. Hsu, P. Reiss, A. Shuman, J. Marks, and J.T. Ngo. Towards practical automated motion synthesis. *Mitsubishi Electr. Res. Labs, TR-94-11*, 1994.
- [17] M.M. Ayoub. A 2-D simulation for lifting activities. *Computers Ind. Engng.*, 35:619–622,, 1998.
- [18] N. Badler. Animation 2000++. *Vision*, pages 28–29, January/February 2000.
- [19] N. Badler, C.B. Phillips, and B.L. Weber. Articulated figure positioning by multiple constraints. *IEEE Comput. Graph.*, 7(6):28–38, 1987.
- [20] N.I. Badler. Virtual humans for animation, ergonomics, and simulation. <http://www.cis.upenn.edu/~badler/vhpaper/vhlong/vhlong.html>, 1997.
- [21] N.I. Badler, R. Bindiganavale, J. Bourne, J. Allbeck, J. Shi, and M. Palmer. Real time virtual humans. <http://www.cis.upenn.edu/~badler/bcs/Paper.htm>.
- [22] P. Baerlocher and R. Boulic. Kinematic control of the mass properties of redundant articulated bodies. *IEEE Int. Conf. on Robotics and Automation 2000, San Francisco (USA)*, pages 2557–2562.
- [23] J.E. Baker and D.D. Thomas. A thermodynamic muscle model and chemical basis for a.v.hill’s muscle equation. *J. Muscle Res. Cell Motility*, 21:335–344, 2000.
- [24] D. Baraff. An introduction to physically based modeling: rigid body simulation. *SIGGRAPH’97 Course Notes*, pages D1–D68, 1997.
- [25] D. Baraff and A. Witkin. Large steps in cloth simulation. *Comput. Graphics*, 32:43–54, August 1998.
- [26] J. Barraquand and J.-C. Latombe. Robot motion planning: a distributed representation approach. *Int. J. Rob. Res.*, 10:628–649, 1991.
- [27] R. Barzel and A.H. Barr. A modeling system based on dynamics. In *Proc. of ACM SIGGRAPH*, pages 179–188, 1988.
- [28] R. Barzel, J.H. Hughes, and D. N. Wood. Plausible motion simulations for computer graphics animation. In R. Boulic and G. Hégron, editors, *Computer Animation and Simulation ’96*, pages 183–197, 1996.
- [29] M. Bediz. A computer simulation study of a single rigid body dynamic model for biped postural control. *Thesis, Naval Postgraduate School, Monterey, California, 160 pp.*, 1997.
- [30] P.I. Begun and Yu.A. Shukeilo. *Biomechanics*. Polytechnika, Saint-Petersburg, 463 pp. (in Russian), 2000.
- [31] N.A. Bernstein. *On the Construction of Movements*. Moscow, Medgiz (In Russian), 1947.
- [32] J.E. Bertram and A. Ruina. Multiple walking speed-frequency relations are predicted by constrained optimization. *J. Theor. Biol.*, 209:445–453, 2001.
- [33] A. G. Bharatkumar, K. E. Daigle, M. G. Pandy, Q. Cai, and J. K. Aggarwal. Lower limb kinematics of human walking with medial axis transformation. In *Proc. of the Workshop on Motion of Non-Rigid and Articulated Objects*, Austin, Texas, 1994.

- [34] A.B. Billard and M. Mataric. Learning human arm movements by imitation: evaluation of a biological-inspired connectionist architecture. In *First IEEE-RAS Int. Conf. Humanoid Robotics (Humanoids-2000)*, Cambridge, MA, 2000.
- [35] E. Bizzi, F.A. Mussa-Ivaldi, and S. Giszter. Computations underlying the execution of movement: a biological perspective. *Science*, 253:287–291, 1991.
- [36] J. Bjornstrup. Estimation of human body segment parameters. Historical background. http://www.vision.auc.dk/jorgen/PhD/EHBSP_background, 1995.
- [37] B. Blumberg and T. Galyean. Multi-level direction of autonomous creature for real-time virtual environments. In *Proc. of SIGGRAPH 95*, pages 47–54, 1995.
- [38] R. Boulic, T.K. Capin, Z. Huang, P. Kalra, B. Lintermann, N. Magnenat-Thalmann, L. Moccozet, T. Molet, I.S. Pandzic, K. Saar, A. Schnitt, J. Shen, and D. Thalmann. The HUMANOID Environment for Interactive Animation of Multiple Deformable Human Character. In *Computer Graphics Forum*, volume 14, 1995.
- [39] R. Boulic, P. Fua, L. Herda, M. Siladhi, J.-S. Monzani, G.P. Nedel, and D. Thalmann. An anatomic human body for motion capture. In *Proc. of EMMSEC98*, Bordeaux, France, 1998.
- [40] R. Boulic, N. Magnenat-Thalmann, and D. Thalmann. Coach-trainee: a new methodology for the correction of predefined motions. *First EUROGRAPHICS Workshop on Simulation and Computer Animation, Lausanne*, 1990.
- [41] R. Boulic, N. Magnenat-Thalmann, and D. Thalmann. A global human walking model with real-time kinematic personalization. *Visual Comput.*, pages 344–358, 1990.
- [42] R. Boulic, N. Magnenat-Thalmann, and D. Thalmann. A robust approach for the center of mass position control with inverse kinetics. *J. of Computers and Graphics*, 20(5), 1996.
- [43] R. Boulic and R. Mas. Hierarchical kinematic behaviors for complex articulated figures. In *Interactive Computer Animation*. Prentice Hall, 1996.
- [44] R. Boulic, R. Mas, and D. Thalmann. Robust position control of the center of mass with second order inverse kinetics. *J. of Computers and Graphics*, 20(6), 1996.
- [45] R. Boulic and D. Thalmann. Combined direct and inverse kinematic control for articulated figures motion editing. *Comput. Graph. Forum*, 11(4):189–202, 1992.
- [46] M. Brand and A. Hertzmann. Style machines. In *Proc. SIGGRAPH 2000*, pages 183–192, 2000.
- [47] Y. Brenière. Why we walk the way we do. *J. of Motor Behav.*, 28(4):291–298, 1996.
- [48] Y. Brenière. How locomotor parameters adapt to gravity and body structure changes during gait development in children. *Motor Control*, 3:186–204, 1999.
- [49] Y. Brenière. Simulation of gait and gait initiation associated with body oscillating behavior in the gravity environment on the Moon, Mars and Phobos. *Biol. Cybern.*, 84:261–267, 2001.
- [50] Y. Brenière, B. Bril, and R. Fontaine. Analysis of the transition from upright stance to steady-state locomotion in children with under 200 days of autonomous walking. *J. of Motor Behav.*, 21(1):20–37, 1989.

- [51] Y. Brenière and C. Ribreau. A double-inverted pendulum model for studying the adaptivity of postural control to frequency during human stepping in place. *Biol. Cybern.*, 79:337–345, 1998.
- [52] R. Brooks and T. Lozano-Pérez. A subdivision algorithm in configurational space for findpath with rotation. In *Proceeding 8th Joint Conf. on Artificial Intelligence*, pages 799–806, 1983.
- [53] A. Bruderlin. The creative process of animating human movement. *Knowledge-Based Systems*, 9:359–367, 1996.
- [54] A. Bruderlin and T.W. Calvert. Interactive animation of personalized human locomotion. *Computer Interface*, pages 17–23, 1993.
- [55] A. Bruderlin and T.W. Calvert. Knowledge-driven, interactive animation of human running. In *Graphic Interface'96*, pages 213–221, 1996.
- [56] A. Bruderlin and L. Williams. Motion signal processing. In *Proc. of SIGGRAPH'95*, pages 97–104, 1995.
- [57] D. Bullock and S. Grossberg. Neural dynamics of planned arm movements: emergent invariants and speed-accuracy properties during planned arm movements. *Psychol. Rev.*, 95:49–90, 1988.
- [58] T.W. Calvert and J. Chapman. Aspects of the kinematic simulation of human movement. *IEEE Comput. Graph.*, pages 41–50, 1982.
- [59] C. Capelli. Physiological determinants of best performance in human locomotion. *Eur. J. Appl. Physiol.*, 80:298–307, 1999.
- [60] J.E. Chadwick, D.R. Haumann, and R.E. Parent. Layered construction for deformable animated character. *Computer Graphics*, 23:243–252, 1989.
- [61] D.B. Chaffin, J. Faraway, and X. Zhang. Simulating reach motions. In *SAE Human Modeling for Design and Engineering Conf.*, The Hague, The Netherlands, 1999.
- [62] T. Chau. A review of analytical techniques for gait data. Part 1: fuzzy, statistical and fractal methods. Part 2: neural networks and methods. *Gait Posture*, 13:49–66, 102–120, 2001.
- [63] Z. Chen and H.J. Lee. Knowledge-guided visual perception of 3-d human gait from a single image sequence. *IEEE Trans. Sys. Man Cyb.*, 22:336–342, 1992.
- [64] E.J. Cheng, J.E. Brown, and G.E. Loeb. Virtual muscle: a computational approach to understanding the effects of muscle properties on motor control. *J. Neurosci. Methods*, 101(2):117–130, 2000.
- [65] M. Y. Cheng and C. S. Lin. Genetic algorithm for control design of biped locomotion. *J. of Robotic Syst.*, 14(5):365–373, 1997.
- [66] D. Chi, M. Costa, L. Zhao, and N. Badler. the EMOTE model for effort and shape. In *Proc. SIGGRAPH 2000*, pages 173–182, 2000.
- [67] L. Chou, L. F. Draganich, and S. M. Song. Minimum energy trajectories of the swing ankle when stepping over obstacles of different heights. *J. Biomech.*, 30(2):115–120, 1997.
- [68] A.G. Chowdhary and J.H. Challis. Timing accuracy in human throwing. *J. Theor. Biol.*, 201:219–229, 1999.

- [69] S.-K. Chung. Interactively responsive animation of human walking in virtual environments. *DS Thesis, The George Washington Univ., 90 pp.*, 2000.
- [70] M. Cohen. Interactive spacetime control for animation. In *Proc. of SIGGRAPH'92*, pages 293–302, 1992.
- [71] G.K. Cole, A.J. van der Bogert, W. Herzog, and K.G.M. Gerritsen. Modelling of force production in skeletal muscle undergoing stretch. *J. Biomech.*, 29:1091–1104, 1996.
- [72] L.S. Crawford. Learning control of complex skills. *PhD Thesis, Univ. California, 148 pp.*, 1998.
- [73] G. S. Cymbalyuk, R. M. Borisjuk, U. Mueller-Wilm, and H. Cruse. Oscillatory network controlling six-legged locomotion. Optimization of model parameters. *Neural Networks*, 11((7-8)):1449–1460, 1998.
- [74] A. Daldegan, N. Magnenat-Thalmann, T. Kurihara, and D. Thalmann. An integrated system for modeling, animating and rendering hair. *Comput. Graph. Forum*, 12(3):211–221, 1993.
- [75] M.H.E. de Lussanet and R. McN. Alexander. A simple model for fast planar arm movements; optimizing mechanical activation and moment-arms of uniarticular and biarticular arm muscles. *J. Theor. Biol.*, 184:187–201, 1997.
- [76] S. Dehandtschutter and O. Verkerckmoes. Efficient control of a musculotendon human model. In *Proc. of the 6th Int. Symp. on the 3D Analysis of Human Movement*, pages 13–16, Cape Town, South Africa, 2000.
- [77] W.T. Dempster and G.R.L. Gaughran. Properties of body segments based on size and weight. *Am. J. Anat.*, 120:33–54, 1965.
- [78] G. Deunne, M. Desbrun, M.-P. Sani, and A.H. Barr. Dynamic real-time deformations using space & time adaptive sampling. In *Proc. of SIGGRAPH 2001*, 2001.
- [79] F. J. Diedrich and W. H. Warren. The dynamics of gait transitions: Effects of grade and load. *J. of Motor Behav.*, 30(1):60–78, 1998.
- [80] M. R. Dimitrijevic, J. Gerasimenko, and M. M. Pinter. Evidence for a spinal central pattern generator in humans. *Ann. New York Acad. Sci.*, 860:360–376, 1998.
- [81] N.V. Dounskaia, S.P. Swinnen, C.B. Walter, A.J. Spaepen, and S.M.P. Verschueren. Hierarchical control of different elbow-wrist coordination patterns. *Exp. Brain Res.*, 121:239–254, 1998.
- [82] J. Duysens and H. Van de Crommert. Neural control of locomotion. Part 1. The central pattern generator from cats to humans. *Gait Posture*, 7:131–141, 1998.
- [83] B. Eberhard, A. Weber, and W. Strasser. A fast, flexible, particle-system model for cloth drapping. *IEEE Comput. Graph.*, 16:52–59, 1996.
- [84] P. Eberhard, T. Spägle, and A. Gollhofer. Investigations for the dynamical analysis of human motion. *Multibody Syst. Dyn.*, 3:1–20, 1999.
- [85] J. J. Eng, D. A. Winter, and A. E. Patla. Intralimb dynamics simplify reactive control strategies during locomotion. *J. Biomech.*, 30(6):581–588, 1997.
- [86] G.J.C. Ettema and K. Meijzer. Muscle contraction history: modified hill versus an exponential decay model. *Biol. Cybern.*, 83:491–500, 2000.

- [87] F. Faure, G. Debunne, M.-P. Cani-Gascuel, and F. Multon. Dynamic analysis of human walking. In *8th Eurographics Workshop on Computer Animation and Simulation*, Sep 1997.
- [88] D.P. Ferris, K. Liang, and C. T. Farley. Runners adjust leg stiffness for their first step on a new running surface. *J. Biomech.*, 32:787–794, 1999.
- [89] E. Forster, T. Müller, H. Steffan, and B. Geigl. Numerical simulation of the human ankle, the subtalar and the midtalar joints. In *Proc. of the 6th Int. Symp. on the 3D Analysis of Human Movement*, pages 77–81, Cape Town, South Africa, 2000.
- [90] C. Frohlich. Do springboard divers violate angular momentum conservation? *Am. J. Phys.*, 47:583–592, 1979.
- [91] R. Full and D. E Koditschek. Templates and anchors: neuromechanical hypotheses of legged locomotion on land. *J. Exper. Biol.*, 202:3325–3332, 1999.
- [92] R.J. Full and M.S Tu. Mechanics of six-legged runners. *J. Exper. Biol.*, pages 129–146, 1990.
- [93] J.D. Funge. Making them behave. Cognitive models for computer animation. *PhD Thesis, Univ. Toronto, 121 pp.*, 1998.
- [94] M.S. Garsia. Stability, scaling, and chaos in passive-dynamic gait models. *PhD thesis, Cornell Univ.*, 1999.
- [95] G.C.-H. Chuang and C.-C. J. Kuo. Cartoon animation and morphing with wavwlet curve descriptor. *Multidim. Systems Signal Process.*, 8:423–447, 1997.
- [96] M. Girard and A.A. Maciejewski. Computational modeling for the computer animation of legged figures. In *Proc. of SIGGRAPH'85*, pages 263–270, 1985.
- [97] M. Gleicher. Comparative analysis of constrained-based motion editing methods. In *Proc. of Int. Workshop on Human Modeling and Animation*, Seoul, Korea, 2000.
- [98] M. Gleicher and P. Litwinowicz. Constrained-based motion adaptation. *J. of Visual. Comp. Animat.*, 9:65–94, 1998.
- [99] D. Goldberg. *Genetic Algorithms in Search, Optimization and Machine Learning*. Addison Wesley, 1989.
- [100] S. Goldstein, E. Large, and D. Metaxas. Non-linear dynamical system approach to behavior modeling. *Visual Comput.*, 15:349–354, 1999.
- [101] G.L. Gottlieb, Q. Song, G.I. Almeida, D.-A. Hong, and D. Corcos. Directional control of planar arm movement. *J. Neurophysiol.*, 78:2985–2998, 1997.
- [102] J.P. Granieri, W. Becket, B.J. Reich, J. Crabtree, and N.I. Badler. Behavioral control for real-time simulated human agents. In *Proc. of Symp. Interactive 3D Graphics*, Monterey, USA, 1995.
- [103] J.P. Granieri, J. Crabtree, and N.I. Badler. Production and playback of human figure motion for visual simulation. In *Proc. of Virtual Reality Int. Symp.*, 1995.
- [104] F.S. Grassia. Believable automatically synthesized motion by knowledge-enhanced motion transformation. *PhD thesis. Carnegie Mellon Univ.*, 203 pp., 2000.
- [105] A. Gregory, A. State, M. Lin, D. Manocha, and M. Livingston. Feature-based surface decomposition for correspondence and morphing between polyhedra. In *Proc. of Computer Animation'98*, pages 64–71, 1998.

- [106] L. Gritz. Evolutionary controller synthesis for 3-d character animation. *DS Thesis, The George Washington Univ., 103 pp.*, 1999.
- [107] L. Gritz and J. K. Hahn. Genetic programming for articulated figure motion. *J. Visual. Comp. Animat.*, 6:129–142, 1995.
- [108] L. Gritz and J. K. Hahn. Genetic programming evolution of controllers for 3-D character animation. In *Genetic Programming 1997: Proc. of the 2nd Annual Conf.*, pages 139–146, 1997.
- [109] R. Grzeszczuk, D. Terzopoulos, and G. Hinton. NeuroAnimator: a fast neural emulation and control of physics-based models. In *Proc. of SIGGRAPH 98*, pages 9–20, 1998.
- [110] S. Hadap and N. Magnenat-Thalmann. State of the art in hair simulation. In *Proc. of Int. Workshop on Human Modeling and Animation*, pages 3–9, Seoul, Korea, 2000.
- [111] S. Hadap and N. Magnenat-Thalmann. Modeling dynamic hair as a continuum. *Eurographics*, 20(3), 2001.
- [112] D. Halperin, J.C. Latombe, and R. Motwani. Dynamic maintenance of kinematic structures. In J.P. Laumond and M. Overmars, editors, *Algorithms for Robotic Motion and Manipulation*, pages 155–170. A K Peters Publishing, 1997.
- [113] K. Hase and N. Yamazaki. Computational evolution of human bipedal walking by a neuro-musculo-skeletal model. In *Proc. 3rd Int. Symp. Artificial Life and Robotics*, pages 174–177, 1998.
- [114] H. Hatze. Biomechanics of sport – selected examples of successful applications and future perspectives. In *Proc. XVI Int. Symp. on Biomechanics in Sports*, pages 2–22, Konstanz, 1998.
- [115] H. Hatze. The inverse dynamics problem of neuromuscular control. *Biol. Cybern.*, 82:133–141, 2000.
- [116] S. Helava. *Private communication*, 2001.
- [117] S. Henry-Biskup. Anatomically correct character modeling. *Gamasutra*, 2(45), 1998.
- [118] W. Herzog. Force production in the human skeletal muscle. pages 269–281. *Human Kinetics*, 2000.
- [119] D. Hestens. Invariant body kinematics: I. Saccadic and compensatory eye movements. II. Reaching and Neurogeometry. *Neural Networks*, 7:65–77, 79–88, 1994.
- [120] A.V. Hill. The heat of shortening and dynamic constants of muscle. *Proc. Roy. Soc. Lond. (B)*, 126:136–195, 1938.
- [121] J.K. Hodgins. Three-dimensional human running. In *Proc. IEEE Conf. on Robotics and Automation*, 1996.
- [122] J.K. Hodgins and N.S. Pollard. Adapting simulated behaviors for new characters. *Comput. Graphics*, 31:153–162, August 1997.
- [123] J.K. Hodgins, W.L. Wooten, D.C. Brogan, and J.F. O’Brien. Animating human athletics. *Comput. Graphics*, 29:71–78, November 1995.
- [124] D. Hogg. Model-based vision: a program to see a walking person. *Image Vision Comput.*, 1:5–20, 1983.

- [125] A. Hreljac. Determinant of the gait transition speed during human locomotion: kinematic factors. *J. Biomech.*, 28:669–677, 1995.
- [126] D. Hsu, L.E. Kavraki, J.-C. Latombe, R. Motwani, and S. Sorkin. On finding narrow passages with probabilistic roadmap planners. *Robotics: The Algorithm Perspective*, pages 141–153, 1998.
- [127] D. Hsu, R. Kindel, J.-C. Latombe, and S. Rock. Randomized kinodynamic motion planning with moving obstacles. In *The 4th Int. Workshop on Algorithmic Foundation of Robotics*, 2000.
- [128] D. Hsu, J.-C. Latombe, and R. Motwani. Path planning in expansive configuration spaces. In *Proc. IEEE Int. Conf. on Robotics and Automation*, pages 2719–2726, 1997.
- [129] J. Hu, J. Pratt, and G. Pratt. Adaptive dynamic control of a bipedal walking robot with radial basis function neural networks. In *Proc. IEEE/RSJ Int. Conf. on Intelligent Robots Systems*, pages 400–405, Piscataway, NJ, 1998.
- [130] P.S. Huang and M. Van de Panne. A search algorithm for planning dynamic motions. In *Computer Animation and Simulation'96*, pages 169–182, 1996.
- [131] A.F. Huxley. Muscle structure and theories of contraction. *Prog. Biohys.*, 7:255–317, 1957.
- [132] P. Isaacs and M. Cohen. Controlling dynamics simulations with kinematic constraints, behavior functions and inverse dynamics. In *Proc. of SIGGRAPH'87*, pages 215–224, 1987.
- [133] S. Ito, H. Yuasa, Z. w. Luo, M. Ito, and D. Yanagihara. A mathematical model of adaptive behavior in quadruped locomotion. *Biol. Cybern.*, 78:337–347, 1998.
- [134] S.L. Van Sint Jan and G.J. Clewley. Visualization of combined motions in human joints. *IEEE Comput. Graph.*, 18:10–14, November/December 1998.
- [135] S. Jianhua and D. Thalmann. Interactive shape design using metaballs and splines. In *Proc. Implicit Surfaces 95*, Grenoble, 1995.
- [136] D.C. Johanson and M.A. Edey. *LUCY. The beginning of Humankind*. Warner Books, 1981.
- [137] S. Jonic, T. Janjovic, V. Gajic, and D. Popovic. Three machine learning techniques for automatic determination of rules to control locomotion. *IEEE Trans. Biomedical Eng.*, 46(3):300–310, 1999.
- [138] T.R. Kane and M.P. Scher. A dynamic explanation of the falling cat phenomenon. *Int. J. Solids Struct.*, 5:663–670, 1969.
- [139] Y.-M. Kang, H.-G. Cho, and E.-T. Lee. An efficient control over human running animation with extension for planar hopper model. *The J. Visual. Comp. Animat.*, 10:215–224, 1999.
- [140] P. Karla, N. Magnenat Thalmann, L. Moccozet, G. Sannier, A. Aubel, and D. Thalmann. Real-time animation of realistic virtual humans. *IEEE Comput. Graph.*, 18(5):42–55, 1998.
- [141] A. Karniel and G.F. Inbar. A model for learning human reaching movements. *Biol. Cybern.*, 77:173–183, 1997.
- [142] L.E. Kavraki, J.-C. Latombe, R. Motwani, and P. Raghavan. Probabilistic roadmaps for path planning in high-dimensional configurational spaces. *IEEE Trans. Robotics Autom.*, 12:566–580, 1996.

- [143] M. Kawato. Internal models for motor control and trajectory planning. *Current Opinion in Neurobiology*, 9:718–727, 1999.
- [144] F. A. Keijzer. Doing without representations which specify what to do. *Phil. Psych.*, 11(3):269–302, 1998.
- [145] T. M. Kepple, H. J. Sommer, K. L. Siegel, and S. J. Stanhope. A three-dimensional musculoskeletal database for the lower extremities. *J. Biomech.*, 31(1):77–80, 1998.
- [146] E. Klavins, H. Komsuoglu, R. Full, and D. E. Koditschek. *Neurotechnology for Biomimetic Robots*, chapter The Role of Reflexes Versus Central Pattern Generators in Dynamical Legged Locomotion. MIT Press, 2000. *to appear*.
- [147] J.T. Klosowski, M. Held, J.S.B. Mitchel, H. Sowizral, and K. Zikan. Efficient collision detection using bounding volume hierarchies of k-dops. *IEEE Trans. Vis. Comput. Gr.*, 4:21–36, 1998.
- [148] H. Ko. Kinematic and dynamic techniques for analyzing, predicting, and animating human locomotion. *Ph.D. Thesis, Univ. Pennsylvania, 152 pp.*, 1994.
- [149] H. Ko and N.I. Badler. Animating human locomotion in real-time using inverse dynamics. *IEEE Comput. Graph.*, 16:50–59, 1996.
- [150] Y. Koga, K. Kondo, J. Kuffner, and J.-C. Latombe. Planning motions with intentions. In *Proc. of SIGGRAPH'94*, pages 395–408, 1994.
- [151] T. Komura, Y. Shinagawa, and T.L. Kuhl. Creating and retargetting motion by the musculoskeletal human body model. *Visual Comput.*, 16:254–270, 2000.
- [152] S. Kopp and I. Wachsmuth. Planning and motion control in lifelike gestures: a refined approach. In *Proc. of Computer Animation 2000*, pages 104–111, Philadelphia, USA, 2000.
- [153] B. Krabbe, R. Farkas, and W. Baumann. Influence of inertia on intersegment moments of the lower extremity joints. *J. Biomech.*, pages 517–519, 1997.
- [154] P.A. Kramer and G.G. Eck. Locomotor energetics and leg length in hominid bipedality. *J. Hum. Evol.*, 38:651–666, 2000.
- [155] A.D. Kuo. A least squares estimation approach to improving the precision of inverse dynamics computations. <http://www-personal.engin.umich.edu/~artkuo/Papers/InverseDynamicsKuo.html>, 1995.
- [156] R. Lake and M. W. Green. Dynamic motion control an articulated figure using quaternion curves. In *First Conf. on CAD and Graphics*, Hangzhou, 1991.
- [157] A. Lamouret and M. van de Panne. Motion synthesis by example. In *Proc. of the 7th Eurographics Workshop on Simulation and Animation*, pages 199–212, 1996.
- [158] E.W. Large, H.I. Christiansen, and R. Bajcsy. Scaling the dynamic approach to path planning and control: competition among behavioral constraints. *Int. J. Robot. Res.*, 18:37–58, 1999.
- [159] J. Lasseter. Principles of traditional animation applied to 3d computer animation. *ACM Comput. Graphics*, 21(4):35–44, 1987.
- [160] J. Laszlo. Controlling bipedal locomotion for computer animation. *MAS Thesis, Univ. Toronto, 112 pp.*, 1996.

- [161] J. Laszlo, M. Van de Panne, and E. Fiume. Limit cycle control and its application to the animation of balancing and walking. In *Proc. of SIGGRAPH'96*, pages 155–162, 1996.
- [162] J. Laszlo, M. Van de Panne, and E. Fiume. Interactive control for physically-based animation. In *Proc. of SIGGRAPH 2000*, pages 155–162, 2000.
- [163] M.L. Latash, A.S. Aruin, and V.M. Zatsiorsky. The basis of a simple synergy: reconstruction of joint equilibrium trajectories during unrestrained arm movements. *Human Movement Sci.*, 18:3–30, 1999.
- [164] J.-C. Latombe. Motion planning: A journey of robots, molecules, digital actors, and other artifacts. <http://citeseer.nj.nec.com/251358.html>.
- [165] J.-C. Latombe. *Robot motion planning*. Kluwer Academic Pub., 1991.
- [166] G.S. Lee. Towards an integration of computer simulation with computer graphics. In *Skigraph 99 – Western Comp. Graph. Symp.*, Sunshine Village, Canada, 1999.
- [167] J. Lee. A hierarchical approach to motion analysis and synthesis for articulated figures. *PhD thesis, Korea Advan. Inst. Sci. Techn.*, 94 pp., 1999.
- [168] J. Lee and S.Y. Shin. Hierarchical approach to interactive motion editing for human-like figures. In *Proc. of SIGGRAPH'99*, pages 39–48, 1999.
- [169] M.A. Lemay and P.E. Crago. A dynamic model for simulating movements of the elbow, forearm, and wrist. *J. Biomechanics*, 29:1319–1330, 1996.
- [170] M. K. Leung and Y.-H. Yang. First sight: A human body outline labeling system. *IEEE Trans. Pattern Anal.*, 21(4):359–377, 1999.
- [171] J.P. Lewis, M. Cordner, and N. Fong. Pose space deformation: a unified approach to shape interpolation and skeleton-driven deformation. In *Proc. of SIGGRAPH 2000*, pages 165–172, 2000.
- [172] G. Li, K. R. Kaufman, F. Chao, and H. E. Rubash. Prediction of antagonistic muscle forces using inverse dynamic optimization during flexion extension of the knee. *J. Biomech. Engng.*, 121(3):316–322, 1999.
- [173] R.L. Lieber. Skeletal muscle is a biological example of a linear electro-active actuator. In *Proc. 6th SPIE Ann. Int. Symp. Smart Struct. Mater., Paper N 3669-03*, San Diego, 1999.
- [174] S. Lien and J. Kajiya. A symbolic method for calculation the integral properties of arbitrary non-convex polyhedra. *IEEE Comput. Graph.*, 4(5):35–41, 1984.
- [175] I.S. Lim and D. Thalmann. Solve customer's problems: interactive evolution for tinkering with computer animation. In *Proc. ACM Symp. Appl. Comput.*, pages 404–407, 2000.
- [176] N. Lindsay. Modelling of the Shoulder Mechanism. *Report no. 106, Institute Mech. Eng., Aalborg Univ., Denmark*, 2001.
- [177] Z. Liu, S. Gortler, and M. Cohen. Hierarchical spacetime control. In *Proc. of SIGGRAPH'94*, pages 35–42, 1994.
- [178] G.E. Loeb, I.E. Brown, and E.J. Cheng EJ. A hierarchical foundation for models of sensorimotor control. *Exp Brain Res.*, 126:1–18, 1999.
- [179] T. Lozano-Pérez. Spatial planning: a configuration space approach. *IEEE Trans. Comput.*, C-32:3–24, 1983.

- [180] T.-W. Lu and J.J. O'Connor. Three-dimensional computer graphics-based modelling and mechanical analysis of the human locomotor system. In *Proc. of the 6th Int. Symp. on the 3D Analysis of Human Movement*, pages 66–69, Cape Town, South Africa, 2000.
- [181] I.N. Lyon and B.L. Day. Control of frontal plane body motion in human stepping. *Exp. Brain Res.*, 115:345–356, 1997.
- [182] G. Maestri. Learning to Walk. The Theory and Practice of 3D Character Motion. <http://www.css.tayloru.edu/instrmat/graphics/hypgraph/animation/walking/learningtowalk.htm>, 1997.
- [183] N. Magnenat-Thalmann, R. Laperriere, and D. Thalmann. Joint-dependent local deformations for hand animation and object grasping. In *Proc. Graphic Interface*, pages 26–33, 1988.
- [184] N. Magnenat-Thalmann and D. Thalmann. Complex models for animating synthetic actors. *IEEE Comput. Graph.*, 11, 1991.
- [185] N. Magnenat-Thalmann and D. Thalmann. Six hundred indexed references on computer animation. *J. Visual. Comp. Animat.*, 2:147–174, 1992.
- [186] K.D. Mai, V. Glauche, C. Beckstein, and R. Bickhan. Controlling fast spring-legged locomotion with artificial neural networks. *Soft Computing*, 4:157–164, 2000.
- [187] W. Maurel. 3d modeling of the human upper limb including the biomechanics of joints, muscles and soft tissues. *Ph.D. Thesis, École Polytechnique Fédérale de Lausanne*, 1998.
- [188] W. Maurel, D. Thalmann, P. Hoffmeyer, P. Beylot, P. Gingins, P. Karla, and N. Magnenat-Thalmann. A biomechanical model of human upper limb modeling for dynamic simulation. In *4th Eurographics Workshop Computer Animation Simulation*, pages 121–136, 1996.
- [189] W. Maurel, Y. Wu, N. Magnenat-Thalmann, and D. Thalmann. *Biomechanical Models for Soft Tissue Simulations*. Springer, 173 pp., 1998.
- [190] B. J. McFadyen and H. Carnahan. Anticipatory locomotor adjustments for accommodating versus avoiding level changes in humans. *Exp. Brain Res.*, 114(3):500–506, 1997.
- [191] T. McGeer. Passive dynamic walking. *Int. J. Robot. Res.*, 9:68–82, 1990.
- [192] M. McKenna and D. Zeltzer. Dynamic simulation of autonomous legged locomotion. *Comput. Graphics*, 24:29–38, 1990.
- [193] M.J. Miller, A. Ali, and K. Ali. Refinement of algorithms for the real-time simulation of human movement in computer models. *Computers Ind. Engng.*, 31:507–509, 1996.
- [194] A.E. Minetti. The three models of terrestrial locomotion. In B.M. Nigg, B.R. Macintosh, and J. Mester, editors, *Biomechanics and Biology of Movement*, pages 67–78. Human Kinetics, 2000.
- [195] A.E. Minetti and R. McN. Alexander. A theory for metabolic costs for bipedal gaits. *J. Theor. Biol.*, 186:467–476, 1997.
- [196] N. Mirtich. V-clip: fast and robust polyhedral collision detection. *ACM Trans. Graphics*, 17:177–208, 1998.

- [197] L. Moccozet and N. Magnenat-Thalmann. Dirichlet free-form deformations and their application to hand simulation. In *Proc. Computer Animation'97*, pages 93–102, 1997.
- [198] T. Molet, R. Boulic, and D. Thalmann. A real time anatomical converter for human motion capture. In *Proc. 7th Eurographics Int. Workshop on Animation and Simulation*, 1996.
- [199] U. Mullerwilm. A neuron-like network with the ability to learn coordinated movement patterns. *Biol. Cybern.*, 68:519–526, 1993.
- [200] F. Multon, L. France, M.-P. Cani-Gascuel, and G. Debunne. Computer animation of human walking: a survey. *INRIA, Rapport de Recherche N 3441, 33 pp.*, 1998.
- [201] F. Multon, S. Ménardais, and B. Arnaldi. Human motion coordination: a juggler as an example. *Visual Comput.*, 17:91–105, 2001.
- [202] L.C. Nedel and D. Thalmann. Modeling and deformation of the human body using an anatomically-based approach. In *Proc. of Computer Animation 98*, pages 34–40, Philadelphia, Pennsylvania, USA, 1998.
- [203] L.C. Nedel and D. Thalmann. Real time muscle deformations using mass-spring systems. In *Proc. of Computer graphics Int. (CGI 98)*, pages 156–165, Hannover, Germany, 1998.
- [204] D.J. Newman and G. Schaffner. Computational dynamic analysis of extravehicular activity (eva): large mass handling. *J. Spacecraft Rockets*, 35:225–227, 1998.
- [205] H.N. Ng and R.L. Grimsdale. Computer graphics techniques for modeling cloth. *IEEE Comput. Graph.*, 16:28–41, 1996.
- [206] V. Ng-Thow-Hing. A biomechanical musculotendon model for animating articulated objects. *MS thesis, Univ. Toronto, 108 pp.*, 1994.
- [207] V. Ng-Thow-Hing and E. Fiume. Interactive display and animation of B-spline solids as muscle shape primitives. In *Eurographics Computer Animation and Simulation Workshop*, 1997.
- [208] J. T. Ngo and J. Marks. Spacetime constraints revisited. In *Proc. of SIGGRAPH 93*, pages 343–350, Anaheim, California, 1993.
- [209] E. Nicholls. Bipedal dynamic walking in robotics. *Thesis, Univ. Western Australia*, 1998.
- [210] B.M. Niggs, B.R. Macintosh, and J. Mester, editors. *Biomechanics and Biology of Movement*. Human Kinetics, 468 pp., 2000.
- [211] J. Nilsson, A. Thorstensson, and J. Halbertsma. Changes in leg movement and muscle activity with speed of locomotion and mode of progression in humans. *Acta Physiol. Scand.*, 123:457–475, 1985.
- [212] T. Noma, K. Oishi, H. Futsuhara, H. Baba, T. Ohashi, and T. Ejima. A motion generator approach to translating human motion from video to animation motion generator approach. *J. Visual. Comp. Animat.*, 11:237–248, 2000.
- [213] N. Ogihara and N. Yamazaki. Generation of human bipedal locomotion by a bio-mimetic neuro-musculo-skeletal model. *Biol. Cybern.*, 84:1–11, 2001.
- [214] J. O'Rourke and N. I. Badler. Model-based image analysis of human motion using constraint propagation. *IEEE Trans. Pattern Anal.*, 2:522–536, 1980.

- [215] M. Oshita and A. Makinouchi. Motion tracking with dynamic simulation. In *Computer Animation and Simulation*, pages 59–71. Springer, 2000.
- [216] L.J. Palmer and R.L. Grimsdale. Collision detection for animation using sphere-trees. *Comput. Graph. Forum*, 14:105–116, 1995.
- [217] M.G. Pandy and N. Berme. A numerical method for simulating the dynamics of human walking. *J. Biomech.*, 21(12):1043–1051, 1988.
- [218] I.S. Pandzic, P. Kalra, and N. Magnenat-Thalmann N. Real time facial interaction. *Displays*, 15(3):157–163, 1994.
- [219] F.C. Park and M.W. Kim. Lie theory, riemannian geometry and dynamics of coupled rigid bodies. *Z. angew. Math. Phys.*, 51:820–834, 2000.
- [220] J. Park and D.S. Fussel. Forward dynamics based realistic animation of rigid bodies. *Comput. Graph.*, 21(4):483–496.
- [221] A.E. Patla, A. Adkin, and T. Ballard. Online steering: coordination and control of body center of mass, head and body orientation. *Exp. Brain Res.*, 129:629–634, 1999.
- [222] A. Pellioniz and R. Llinás. Tensorial network theory of the metaorganization of functional geometry in the nervous system. *Neuroscience*, 16:245–273, 1985.
- [223] C.B. Phillips, N.I. Badler, and B.L. Webber. *Simulating Humans: Computer Graphics, Animation, and Control*. Oxford University Press, 266 pp., 1993.
- [224] R. Plaenkers and P. Fu. Articulated soft objects for video-based body modeling. In *Proc. of 8th Int. Conf. on Computer Vision*, Vancouver, Canada, 2001.
- [225] R.R. Playter. Passive dynamics in the control of gymnastic maneuvers. *Massachusetts Institute of Technology, A.I. Memo No. 1504*, pages 1–185, 1995.
- [226] N.S. Pollard. Simple machines for scaling human motion. In *Eurographics Workshop on Animation and Simulation*, Milan, Italy, 1999.
- [227] N.S. Pollard and F. Behraram-Mosavit. Force-based motion editing for locomotion tasks. In *IEEE Int. Conf. on Robotics and Animation*, San Francisco, 2000.
- [228] N.S. Pollard and J.S.A. Reitsma. Animation of humanlike characters: dynamic motion filtering with a physically plausible contact model. In *Yale Workshop on Adaptive and Learning Systems*, 2001.
- [229] Z. Popović. Controlling physics in realistic character animation. *Commun. ACM*, 43:51–58, 2000.
- [230] Z. Popović and A. Witkin. Physically based motion transformation. In *Proc. of SIGGRAPH'99*, pages 11–20, 1999.
- [231] J. Pratt and G. Pratt. Exploiting natural dynamics in the control of a planar bipedal walking robot. In *Proc. 36th Ann. Allerton Conf. on Communication, Control and Computing*, Monticello, IL, 1998.
- [232] S. D. Prentice, A. E. Patla, and D. A. Stacey. Simple artificial neural network models can generate basic muscle activity patterns for human locomotion at different speeds. *Exper. Brain Res.*, 123(4):474–480, 1998.
- [233] S. D. Prentice, A. E. Patla, and D. A. Stacey. Artificial neural network model for generation of muscle activation patterns for human locomotion. *J. Electromiogr. Kinesiology*, 11:19–30, 2001.

- [234] M.H. Raibert and J.A. Hodgins. Legged robots. In R. Beer, R. Ritzmann, and T. McKenna, editors, *Biological Neural Networks in Invertebrate neuroethology and Robotics*, pages 319–354. Academic Press, 1993.
- [235] P. Ratner. *3-D Human Modeling and Animation*. John Wiley & Sons, 308 pp., 1998.
- [236] B.D. Reich. An architecture for behavioral locomotion. *PhD thesis*, 165 pp., 1997.
- [237] J.A. Reichler and F. Delcomyn. Dynamic simulation and controller interfacing for legged robots. *Int. J. Robotics Res.*, 19(1):41–57, 2000.
- [238] C.W. Reynolds. Steering behaviors for autonomous characters. <http://www.red.com/cwr/>.
- [239] R. Riener and J. Quintern. A physiologically based model of muscle activation verified by electrical stimulation. *Bioelectrochem. Bioenerg.*, 43:257–264, 1997.
- [240] R. Riener, J. Quintern, and G. Schmidt. Biomechanical model of the human knee evaluated by neuromuscular stimulation. *J. Biomech.*, 29:1157–1167, 1996.
- [241] G. Rizoletti, L. Gadiga, V. Gallese, and L. Fogassi. Premotor cortex and recognition of motor actions. *Cognitive Brain Res.*, 3:131–141, 1996.
- [242] K. Rohr. Towards model-based recognition of human movements in image sequences. *Comput. Vis. Image Und.*, 59:94–115, 1994.
- [243] Ch. Rose, B. Guenter, B. Bodenheimer, and M.F. Cohen. Efficient generation of motion transitions using spacetime constraints. In *Proc. of SIGGRAPH'96*, pages 147–154, 1996.
- [244] R. Rosenblum, W. Carlson, and E. Tripp. Simulating the structure and dynamics of human hair: modeling, rendering and animation. *J. Visual. Comp. Animat.*, 2:141–148, 1991.
- [245] N.J. Rubenking. The DQOM phenomenon. *PC Magazine*, 13:314–318, 1994.
- [246] R.L. Sainburg, C. Ghazizadeh, and D. Kalakanis. Intersegmental dynamics are controlled by sequential anticipatory, error correction and posture mechanisms. *J. Neurophysiol.*, 81:1045–1056, 1999.
- [247] M.J. Sanders. Evolving locomotion controllers for virtual creatures. *MS Thesis, Univ. Auckland*, 2000.
- [248] A. Savenko, S. Van Sint Jan, and G. Clapworthy. A biomechanics-based model for the animation of human locomotion. <http://eos.wdcb.ru/cgg/BIOMECHANICS/BIOMECHANICS.htm>, 1999.
- [249] S. Schaal and D. Sternad. Origins and violations of the 2/3 power law in rhythmic 3d arm movements. *Exp. Brain Res.*, 136:60–72, 2001.
- [250] F. Scheepers, R.E. Parent, and W.E. Carlson. Anatomy-based modeling of the human musculature. In *Proc. of SIGGRAPH 97*, 1997.
- [251] G. Schöner and M. Dose. A dynamics system approach to task level system integration used to plan and control autonomous vehicle motion. *Robot. Autonom. Systems*, 10:253–267, 1992.
- [252] G. Schöner, M. Dose, and C. Engels. Dynamics of behavior: theory and application for autonomous robot architectures. *Robot. Autonom. Systems*, 16:213–246, 1996.

- [253] A.F. Schouten, E. de Vlugt, F.C.T. van der Helm, and G.G. Brouwn. Optimal posture control of a musculo-skeletal arm model. *Biol. Cybern.*, 84:143–152, 2001.
- [254] F. Sepulveda, D.M.Wells, and C.L. Vaughan. A neural network representation of electromyography and joint dynamics in human gait. *J. Biomech.*, 26(2):101–109, 1993.
- [255] A. Seyfarth, M. Günter, and R. Blickhan. Stable operation of an elastic three-segment leg. *Biol. Cybern.*, 84:365–382, 2001.
- [256] J. Shi, T. J. Smith, J. Granieri, and N. Badler. Smart avatars in JackMOO. In *Proceedings of IEEE Virtual Reality Conf.*, pages 156–163, 1999.
- [257] Y.P. Shimansky. Spinal motor control system incorporates an internal model of limb dynamics. *Biol. Cybern.*, 83:379–389, 2000.
- [258] V.A. Sholuha, K.J. van Zweiten, P.L. Lippens, and A.V. Zinkovski. Finger tendons kinematics assessing from motion dynamics computer oriented modeling. In *11th Conf. of ESB*, page 29, Toulouse, 1998.
- [259] P.-P. Sloan, Ch.F. Rose, and M.F. Cohen. Shape and animation by example. *Technical report MSR-TR-2000-79*, 22 pp., 2000.
- [260] A. M. Smith. Does the cerebellum learn strategies for the optimal time-varying control of joint stiffness? *Behav. Brain Sci.*, 19(3):399–410, 1996.
- [261] V.V. Smolyaninov. Spatio-temporal problems of locomotion control. *Physics-Uspokhi*, 43(10):991–1053, 2000.
- [262] M.W. Spong. Underactuated mechanical systems. *Control Problems in Robotics and Automation, Lect. Notes in Control and Information Sciences*, 230, 1997.
- [263] R. Stein, E.P. Zehr, and J. Bobet. Basic concepts of movement control. In B.M. Niggs, B.R. Macintosh, and J. Mester, editors, *Biomechanics and Biology of Movement*, pages 163–178. Human Kinetics, 2000.
- [264] D. Sternad and S. Scheuch. Segmentation of endpoint trajectories does not imply segmented control. *Exp. Brain Res.*, 124:118–136, 1999.
- [265] G. Taga. A model of the neuro-musculo-skeletal system for human locomotion. 1. Emergence of basic gait. *Biol. Cybern.*, 73(2):97–111, 1995.
- [266] G. Taga. A model of the neuro-musculo-skeletal system for anticipatory adjustment of human locomotion during obstacle avoidance. *Biol. Cybern.*, 78:9–17, 1998.
- [267] S. Tak, O. y. Song, and H.-S. Ko. Motion balance filtering. In *EUROGRAPHICS 2000*. Blackwell Publishers, 2000.
- [268] J.D. Talbot. Accurate characterization of skin deformations using range data. *MS Thesis, Univ. Toronto*, 84 pp., 1998.
- [269] G. Tevatia and S. Schaal. Inverse kinematics for humanoid robots. In *IEEE Int. Conf. on Robotics and Automation*, San Francisco (USA), 2000.
- [270] N. Magnenat Thalmann and D. Thalmann. Computer animation. In *Handbook of Computer Science*, pages 1300–1318. CRC Press, 1996.
- [271] F. Thomas and O. Johnson. *Disney Animation: The Illusion of Life*. Abbeville Press, New York, 1981.

- [272] E. Todorov. Direct cortical control of muscle activation in voluntary arm movements: a model. *Nature Neuroscience*, 4(3):391–398, 2000.
- [273] E. Todorov and M.I. Jordan. Smoothness maximization along a predefined path accurately predicts the speed profiles of complex arm movements. *J. Neurophysiol.*, 80:696–714, 1998.
- [274] D. Tolani and N. Badler. Real-time inverse kinematics for the human arm. *Presence*, 5(4):393–401, 1996.
- [275] N. Torkos and M. van de Panne. Footprint-based quadruped motion synthesis. In *Graphics Interface*, pages 151–160, 1998.
- [276] T.Spägle, A. Kistner, and A. Gollhofer. Modeling, simulation and optimization of a human vertical jump. *J. Biomech.*, 32:521–530, 1999.
- [277] T.Spägle, A. Kistner, and A. Gollhofer. A multi-phase optimal control technique for the simulation of a human vertical jump. *J. Biomech.*, 32:87–91, 1999.
- [278] G. Turk and J.F. O’Brien. Shape transformation using variational implicit functions. In *Proc. of SIGGRAPH’99*, pages 335–342, 1999.
- [279] R. Turner and D. Thalmann. The elastic surface layer model for animated character construction. In *Proc. Comput. Graphics Int.*, pages 399–412, Lausanne, Switzerland, 1993.
- [280] A. Ude, C.G. Atkeson, and M. Riley. Planning of joint trajectories for humanoid robots using B-spline wavelets. In *IEEE Conf. Robotics and Automation*, San Francisco, 2000.
- [281] M. Unuma, K. Anjyo, and R. Takeuchi. Fourier principles for emotion based human figure animation. In *Proc. of SIGGRAPH’95*, pages 97–104, 1995.
- [282] M. van de Panne and E. Fiume. Sensor-actuator networks. In *Proc. of SIGGRAPH 93*, pages 335–342, 1993.
- [283] M. van de Panne, E. Fiume, and Z. Vranesic. Reusable motion synthesis using state-space controllers. In *Proc. of SIGGRAPH’90*, pages 225–234, 1990.
- [284] M. van de Panne and A. Lamouret. Guided optimization for balanced locomotion. In *6th Eurographics Workshop on Computer Animation and Simulation*, pages 165–177, 1995.
- [285] F.C.T. Van der Helm. Finite element musculoskeletal model of the shoulder mechanism. *J. Biomech.*, 27:551–569, 1994.
- [286] F.C.T. van der Helm. Large-scale musculoskeletal system: sensorimotor integration and optimization. In *Neural Control of Posture and Movement*, pages 407–424. Springer, 2000.
- [287] P. Volino and N. Magnenat-Thalmann. Efficient self-collision detection on smoothly discretized surface animations using geometrical shape regularity. *Comput. Graph. Forum*, 13:155–166, 1994.
- [288] H. Wagner and R. Blickhan. Stabilizing function of skeletal muscles: an analytical study. *J. Theor. Biol.*, 199:163–179, 1999.
- [289] M. Walter and A. Fournier. Growth and animation of polygonal models of animals. In *EUROGRAPHICS’97*, 1997.
- [290] X. Wang, M. Maurin, F. Mazet, N. De Casrto Maia, K. Voinot, J.P. Verriest, and M. Fayet. Three-dimensional modelling of the motion range of axial rotation of the upper arm. *J. Biomech.*, 31:899–908, 1998.

- [291] K. Waters. A muscle model for animating three-dimensional facial expression. *Comput. Graphics*, 21(4):17–24, 1987.
- [292] P. Watson. Human walking model at the Visualization Lab. <http://www.utexas.edu/cc/newsletter/oct97/vislab.html>.
- [293] W.Ch. Westenhofer. Using kinematic clones to control the dynamic simulation of articulated figures. *MS Thesis, The George Washington Univ.*, 1995.
- [294] R.T. Whalen, M.G. Pandy, and F.C. Anderson. Large-scale numerical simulations of human motion. <http://www.nas.nasa.gov/Pubs/TechSums/9293/125.html>.
- [295] D.J. Will and J.K. Hahn. Interpolation synthesis of articulated figure motion. *IEEE Comput. Graph.*, 17:39–45, November/December 1997.
- [296] A. Witkin and M. Kass. Spacetime constraints. In *Proc. of SIGGRAPH'88*, pages 159–168, 1988.
- [297] A. Witkin and Z. Popović. Motion warping. In *Proc. of SIGGRAPH'95*, pages 105–108, 1995.
- [298] G. Wolberg. Image morphing survey. *Visual Comput.*, 14(8/9), 1998.
- [299] D.W. Wolpert, R.C. Miall, and M. Kawato. Internal models in cerebellum. *Trends in Cognitive Science*, 9:338–347, 1998.
- [300] W.L. Wooten and J.K. Hodgins. Animation of human diving. *Comput. Graph. Forum*, 15:3–13, 1996.
- [301] C.R. Wren and A.P. Pentland. *Dynamen: a recursive model of human motion. MIT Media Lab. Tech. Rep. No. 441.*
- [302] Y. Wu, P. Kalra, and N. Magnenat Thalmann. Simulation of static and dynamic wrinkles of skin. In *Proc. Computer Animation 96*, pages 90–97, 1996.
- [303] K. y. Young, J.-F. Lee, and H. J. Jou. Robot learning schemes that trade motion accuracy for command simplification. *Fuzzy Sets Systems*, 110:313–329, 2000.
- [304] Y. Yacoob and L.S. Davis. Learned models for estimation of rigid and articulated human motion from stationary or moving cameras. *Int. J. Comput. Vision*, 12:5–30, 2000.
- [305] Y. Yasumuro, Q. Chen, and K. Chihara. 3D modeling of human hand with motion constraint. In *Proc. Int. Conf. Recent Adv. 3D Digital Imaging Modeling*, pages 275–283, ottawa, Canada, 1997.
- [306] M.R. Yeadon and E.C. Mikulcik. Stability and control of aerial movements. In B.M. Niggs, B.R. Macintosh, and J. Mester, editors, *Biomechanics and Biology of Movement*, pages 211–221. Human Kinetics, 2000.
- [307] F.T.J.M. Zaal, K. Daigle, G.L. Gottlieb, and E. Thelen. An unlearned principle for controlling natural movements. *J. Neurophysiol.*, 82:255–259, 1999.
- [308] F. E. Zajac. Muscle coordination of movement — a perspective. *J. Biomech.*, 26:109–124, 1993.
- [309] F.E. Zajac. Muscle and tendon: Properties, models, scaling and application to biomechanics and motor control. *Crit Rev Biomed Eng.*, 17:359–411, 1989.
- [310] V.M. Zatsiorsky. *Kinematics of Human Motion*. Human Kinetics, 419 pp., 1998.
- [311] V.M. Zatsiorsky, A.S. Aruin, and V.N. Selujanov. *Biomechanics of the Human Muskuloskeleton System*. Fizkultura i Sport, Moscow, 143 pp. (in Russian), 1981.

- [312] M. Žefran, V. Kumar, and C. Croke. Choice of Riemannian metrics for rigid body kinematics. In *Proc. 1996 ASME Design Eng. Tech. Conf. and Computers in Eng. Conf*, Irvine, California, 1996.
- [313] D. Zeltzer. Motor control techniques for figure animation. *IEEE Comput. Graph.*, 2:53–59, 1982.
- [314] D. Zeltzer. Towards an integrated view of 3d computer animation. *Visual Comput.*, 1(4):249–259, 1985.
- [315] J. Zhao and N. Badler. Inverse kinematics positioning using nonlinear programming for highly articulated figures. *ACM Trans. Graphics*, 13:313–336, 1994.
- [316] A.V. Zinkovsly, V.A. Sholuha, and A.A. Ivanov. *Mathematical Modeling and Computer Simulation of Biomechanical Systems*. World Science Publishing, 1996.
- [317] V.B. Zordan and J.K. Hodgins. Tracking and modifying upper-body human motion data with dynamic simulation. In *Computer Animation and Simulation'99*, 1999.

DR.RUPNATHJIK(DR.RUPAK NATH)

Appendix

It is NO use saying "we are doing our best". You have got to succeed in doing what is necessary.
Winston Churchill

The Animator's Eleven Commandments

1. Thou shalt never synthesize a motion that thou can capture
2. Thou shalt never mistake a physically correct motion for a believable one
3. Thou shalt never produce a periodic or symmetric motion
4. Thou shalt never copy the nature, but mimic it
5. Thou shalt exploit hierarchical approach at all stages of animation
6. Thou shalt do the multiresolution analysis of motion of thine and remember that low frequencies are basic motion while high ones are style and personality
7. Thou shalt tell the kinematic movement from the dynamic one
8. Thou shalt let thy character to use natural dynamics and reflex movement whenever possible
9. Thou shalt never do forward dynamics without a proper controller, for chaos and madness await thee at this path

10. Thou shalt override the automatically computed motion by manual input whenever thou are in doubt
11. Thou shalt abandon the hope to develop a universal animation method and remember that large software projects are never finished, only released

DR.RUPNATHJI(DR.RUPAK NATH)